

12-15-03

10672183

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 9/45		A1	(11) International Publication Number: WO 98/59292
			(43) International Publication Date: 30 December 1998 (30.12.98)
(21) International Application Number: PCT/US97/11616		(81) Designated States: CA, CN, DE, GB, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 25 June 1997 (25.06.97)			
(71) Applicant: TRANSMETA CORPORATION [US/US]; 3940 Freedom Circle, Santa Clara, CA 95054 (US).		Published <i>With international search report.</i>	
(72) Inventors: CMELIK, Robert, F.; 1024 Chula Vista Terrace, Sunnyvale, CA 94086 (US). DITZEL, David, R.; 4010 Page Mill Road, Los Altos Hills, CA 94022 (US). KELLY, Edmund, J.; 3251 Pinot Blanc Way, San Jose, CA 95135 (US). HUNTER, Colin, B.; 1200 Hamilton Avenue, Palo Alto, CA 94301 (US). LAIRD, Douglas, A.; 16981 Cypress Way, Los Gatos, CA 95032 (US). WING, Malcolm, John; Apartment 5, 24 Kent Place, Menlo Park, CA 94025 (US). ZYNER, Gregorz, B.; 5621 West Walbrook Drive, San Jose, CA 95129 (US).			
(74) Agent: KING, Stephen, L.; 30 Sweetbay Road, Rancho Palos Verdes, CA 90275 (US).			

RECEIVED

MAR - 7 2000

D'ALESSANDRO & ASSOCIATES

(54) Title: **IMPROVED MICROPROCESSOR**

(57) Abstract

A microprocessor for a host computer designed to execute target application programs including the combination of code morphing software, and morph host hardware designed to execute instructions of a host instruction set, the combination translating a target instruction set into a host instruction set, optimizing the host instruction set speculating upon the occurrence of a condition, determining under control of the code morphing software official state of the target computer, updating state of the target computer from state of the host computer when a set of host instructions executes in accordance with the speculation, detecting failure of the condition during execution, updating state from the state of the target computer when a set of host instruction fails to execute in accordance with the speculation, and translating a new set of host instructions without the speculation when a set of host instructions fails to execute in accordance with the speculation.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

IMPROVED MICROPROCESSOR

BACKGROUND OF THE INVENTION

Field Of The Invention

5 This invention relates to computer systems and, more particularly, to methods and apparatus for providing an improved microprocessor.

History Of The Prior Art

There are thousands of application programs which run on computers designed around particular families of microprocessors. The largest
10 number of programs in existence are designed to run on computers (generally referred to as "IBM Compatible Personal Computers") using the "X86" family of microprocessors (including the Intel® 8088, Intel 8086, Intel 80186, Intel 80286, i386, i486, and progressing through the various Pentium® microprocessors) designed and manufactured by
15 Intel Corporation of Santa Clara, California. There are many other examples of programs designed to run on computers using other families of processors. Because there are so many application programs which run on these computers, there is a large market for microprocessors capable of use in such computers, especially
20 computers designed to process X86 programs. The microprocessor market is not only large but also quite lucrative.

Although the market for microprocessors which are able to run large numbers of application programs is large and lucrative, it is quite difficult to design a new competitive microprocessor. For example,
25 even though the X86 family of processors has been in existence for a number of years and these processors are included in the majority of computers sold and used, there are few successful competitive

microprocessors which are able to run X86 programs. The reasons for this are many.

In order to be successful, a microprocessor must be able to run all of the programs (including operating systems and legacy programs) designed for that family of processors as fast as existing processors without costing more than existing processors. In addition, to be economically successful, a new microprocessor must do at least one of these things better than existing processors to give buyers a reason to choose the new processor over existing proven processors.

It is difficult and expensive to make a microprocessor run as fast as state of the art microprocessors. Processors carry out instructions through primitive operations such as loading, shifting, adding, storing, and similar low level operations and respond only to such primitive instructions in executing any instruction furnished by an application program. For example, a processor designed to run the instructions of a complicated instruction set computer (CISC) such as a X86 in which instructions may designate the process to be carried out at a relatively high level have historically included read only memory (ROM) which stores so-called micro-instructions. Each micro-instruction includes a sequence of primitive instructions which when run in succession bring about the result commanded by the high level CISC instruction. Typically, an "add A to B" CISC instruction is decoded to cause a look up of an address in ROM at which a micro-instruction for carrying out the functions of the "add A to B" instruction is stored. The micro-instruction is loaded, and its primitive instructions are run in sequence to cause the "add A to B" instruction to be carried out. With such a CISC computer, the primitive operations within a micro-instruction can never be changed

during program execution. Each CISC instruction can only be run by decoding the instruction, addressing and fetching the micro-instruction, and running the sequence of primitive operations in the order provided in the micro-instruction. Each time the micro-instruction is run, the same sequence must be followed.

State of the art processors for running X86 applications utilize a number of techniques to provide the fastest processing possible at a price which is still economically reasonable. Any new processor which implements known hardware techniques for accelerating the speed at which a processor may run must increase the sophistication of the processing hardware. This requires increasing the cost of the hardware.

For example, a superscalar microprocessor which uses a plurality of processing channels in order to execute two or more operations at once has a number of additional requirements. At the most basic level, a simple superscalar microprocessor might decode each application instruction into the micro-instructions which carry out the function of the application instruction. Then, the simple superscalar microprocessor schedules two micro-instructions to run together if the two micro-instructions do not require the same hardware resources and the execution of a micro-instruction does not depend on the results of other micro-instructions being processed.

A more advanced superscalar microprocessor typically decodes each application instruction into a series of primitive instructions so that those primitive instructions may be reordered and scheduled into the most efficient execution order. This requires that each individual primitive operation be addressed and fetched. To accomplish

reordering, the processor must be able to ensure that a primitive instruction which requires data resulting from another primitive instruction is run after that other primitive instruction produces the needed data. Such a superscalar microprocessor must assure that
5 two primitive instructions being run together do not both require the same hardware resources. Such a processor must also resolve conditional branches before the effects of branch operations can be completed.

Thus, superscalar microprocessors require extensive hardware to
10 compare the relationships of the primitive instructions to one another and to reorder and schedule the sequence of the primitive instructions to carry out any instruction. As the number of processing channels increases, the amount and cost of the hardware to accomplish these superscalar acceleration techniques increases approximately
15 quadratically. All of these hardware requirements increase the complexity and cost of the circuitry involved. As in dealing with micro-instructions, each time an application instruction is executed, a superscalar microprocessor must use its relatively complicated addressing and fetching hardware to fetch each of these primitive
20 instructions, must reorder and reschedule these primitive instructions based on the other primitive instructions and hardware usage, and then must execute all of the rescheduled primitive instructions. The need to run each application instruction through the entire hardware sequence each time it is executed limits the speed at which a
25 superscalar processor is capable of executing its instructions.

Moreover, even though these various hardware techniques increase the speed of processing, the complexity involved in providing such hardware significantly increases the cost of such a microprocessor.

For example, the Intel i486 DX4 processor uses approximately 1.5 million transistors. Adding the hardware required to accomplish the checking of dependencies and scheduling necessary to process instructions through two channels in a basic superscalar
5 microprocessor such as the Intel Pentium® requires the use of more than three million transistors. Adding the hardware to allow reordering among primitive instructions derived from different target instructions, provide speculative execution, allow register renaming, and provide branch prediction increases the number of transistors to
10 over six million in the Intel Pentium Pro™ microprocessor. Thus, it can be seen that each hardware addition to increase operation speed has drastically increased the number of transistors in the latest state of the art microprocessors.

Even using these known techniques may not produce a
15 microprocessor faster than existing microprocessors because manufacturers use most of the economically feasible techniques known to accelerate the operation of existing microprocessors. Consequently, designing a faster processor is a very difficult and expensive task.

20 Reducing the cost of a processor is also very difficult. As illustrated above, hardware acceleration techniques which produce a sufficiently capable processor are very expensive. One designing a new processor must obtain the facilities to produce the hardware. Such facilities are very difficult to obtain because chip manufacturers do not typically
25 spend assets on small runs of devices. The capital investment required to produce a chip manufacturing facility is so great that it is beyond the reach of most companies.

Even though one is able to design a new processor which runs all of the application programs designed for a family of processors at least as fast as competitive processors, the price of competitive processors includes sufficient profit that substantial price reductions are sure to be faced by any competitor.

Although designing a competitive processor by increasing the complexity of the hardware is very difficult, another way to run application programs (target application programs) designed for a particular family of microprocessors (target microprocessors) has been to emulate the target microprocessor in software on another faster microprocessor (host microprocessor). This is an incrementally inexpensive method of running these programs because it requires only the addition of some form of emulation software which enables the application program to run on a faster microprocessor. The emulator software changes the target instructions of an application program written for the target processor family into host instructions capable of execution by the host microprocessor. These changed instructions are then run under control of the operating system on the faster host microprocessor.

There have been a number of different designs by which target applications may be run on host computers with faster processors than the processors of target computers. In general, the host computers executing target programs using emulation software utilize reduced instruction set (RISC) microprocessors because RISC processors are theoretically simpler and consequently can run faster than other types of processors.

However, even though RISC computer systems running emulator software are often capable of running X86 (or other) programs, they usually do so at a rate which is substantially slower than the rate at which state of the art X86 computer systems run the same programs.

5 Moreover, often these emulator programs are not able to run all or a large number of the target programs available.

The reasons why emulator programs are not able to run target programs as rapidly as the target microprocessors is quite complicated and requires some understanding of the different

10 emulation operations. Figure 1 includes a series of diagrams representing the different ways in which a plurality of different types of microprocessors execute target application programs.

In Figure 1(a), a typical CISC microprocessor such as an Intel X86 microprocessor is shown running a target application program which

15 is designed to be run on that target processor. As may be seen, the application is run on the CISC processor using a CISC operating system (such as MS DOS, Windows 3.1, Windows NT, and OS/2 which are used with X86 computers) designed to provide interfaces by which access to the hardware of the computer may be gained.

20 Typically, the instructions of the application program are selected to utilize the devices of the computer only through the access provided by the operating system. Thus, the operating system handles the manipulations which allow applications access to memory and to the various input/output devices of the computer. The target computer

25 includes memory and hardware which the operating system recognizes, and a call to the operating system from a target application causes an operating system device driver to cause an expected operation to occur with a defined device of the target

computer. The instructions of the application execute on the processor where they are changed into operations (embodied in microcode or the more primitive operations from which microcode is assembled) which the processor is capable of executing. As has been
5 described above, each time a complicated target instruction is executed, the instruction calls the same subroutine stored as microcode (or as the same set of primitive operations). The same subroutine is always executed. If the processor is a superscalar, these primitive operations for carrying out a target instruction can often be
10 reordered by the processor, rescheduled, and executed using the various processing channels in the manner described above; however, the subroutine is still fetched and executed.

In Figure 1(b), a typical RISC microprocessor such as a PowerPC microprocessor used in an Apple Macintosh computer is represented
15 running the same target application program which is designed to be run on the CISC processor of Figure 1(a). As may be seen, the target application is run on the host processor using at least a partial target operating system to respond to a portion of the calls which the target application generates. Typically these are calls to the application-like
20 portions of the target operating system used to provide graphical interfaces on the display and short utility programs which are generally application-like. The target application and these portions of the target operating system are changed by a software emulator such as Soft PC® which breaks the instructions furnished by the target
25 application program and the application-like target operating system programs into instructions which the host processor and its host operating system are capable of executing. The host operating system

provides the interfaces through which access to the memory and input/output hardware of the RISC computer may be gained.

However, the host RISC processor and the hardware devices associated with it in a host RISC computer are usually quite different than are the devices associated with the processor for which the target application was designed; and the various instructions provided by the target application program are designed to cooperate with the device drivers of the target operating system in accessing the various portions of the target computer. Consequently, the emulation program, which changes the instructions of the target application program to primitive host instructions which the host operating system is capable of utilizing, must somehow link the operations designed to operate hardware devices in the target computer to operations which hardware devices of the host system are capable of implementing. Often this requires the emulator software to create virtual devices which respond to the instructions of the target application to carry out operations which the host system is incapable of carrying out because the target devices are not those of the host computer. Sometimes the emulator is required to create links from these virtual devices through the host operating system to host hardware devices which are present but are addressed in a different manner by the host operating system.

Target programs when executed in this manner run relatively slowly for a number of reasons. First, each target instruction from a target application program and from the target operating system must be changed by the emulator into the host primitive functions used by the host processor. If the target application is designed for a CISC machine such as an X86, the target instructions are of varying lengths

and quite complicated so that changing them to host primitive instructions is quite involved. The original target instructions are first decoded, and the sequence of primitive host instructions which make up the target instructions are determined. Then the address (or
5 addresses) of each sequence of primitive host instructions is determined, each sequence of the primitive host instructions is fetched, and these primitive host instructions are executed in or out of order. The large number of extra steps required by an emulator to change the target application and operating system instructions into
10 host instructions understood by the host processor must be conducted each time an instruction is executed and slows the process of emulation.

Second, many target instructions include references to operations conducted by particular hardware devices which function in a
15 particular manner in the target computer, hardware which is not available in the host computer. To carry out the operation, the emulation software must either make software connections to the hardware devices of the host computer through the existing host operating system or the emulator software must furnish a virtual
20 hardware device. Emulating the hardware of another computer in software is very difficult. The emulation software must generate virtual devices for each of the target application calls to the host operating system; and each of these virtual devices must provide calls to the actual host devices. Emulating a hardware device requires that
25 when a target instruction is to use the device, the code representing the virtual device required by that instruction be fetched from memory and run to implement the device. Either of these methods of solving

the problem adds another series of operations to the execution of the sequence of instructions.

Complicating the problem of emulation is the requirement that the target application take various exceptions which are carried out by hardware of the target computer and the target operating system in order for the computer system to operate. When a target exception is taken during the operation of a target computer, state of the computer at the time of the exception must be saved typically by calling a microcode sequence to accomplish the operation, the correct exception handler must be retrieved, the exception must be handled, then the correct point in the program must be found for continuing with the program. Sometimes this requires that the program revert to the state of the target computer at the point the exception was taken, and at other times a branch provided by the exception handler is taken. In any case, the hardware and software of the target computer required to accomplish these operations must somehow be provided in the process of emulation. Because the correct target state must be available at the time of any such exception for proper execution, the emulator is forced to keep accurate track of this state at all times so that it is able to correctly respond to these exceptions. In the prior art, this has required executing each instruction in the order provided by the target application because only in this way could correct target state be maintained.

Moreover, prior art emulators have always been required to maintain the order of execution of the target application for other reasons.

Target instructions can be of two types, ones which affect memory or ones which affect a memory mapped input/output (I/O) device. There is no way to know without attempting to execute an instruction

whether an operation is to affect memory or a memory-mapped I/O device. When instructions operate on memory, optimizing and reordering is possible and greatly aids in speeding the operation of a system. However, operations affecting I/O devices often must be practiced in the precise order in which those operations are programmed without the elimination of any steps or they may have some adverse effect on the operation of the I/O device. For example, a particular I/O operation may have the effect of clearing an I/O register. If the operations take place out of order so that a register is cleared of a value which is still necessary, then the result of the operation may be different than the operation commanded by the target instruction. Without a means to distinguish memory from memory mapped I/O, it is necessary to treat all instructions as though they affect memory mapped I/O. This severely restricts the nature of optimizations that are achievable. Because prior art emulators lack both means to detect the nature of the memory being addressed and means to recover from such failures, they are required to proceed sequentially through the target instructions as though each operation affects memory mapped I/O. This greatly limits the possibility of optimizing the host instructions.

Another problem which limits the ability of prior art emulators to optimize the host code is caused by self-modifying code. If a target instruction has been changed to a sequence of host instructions which in turn write back to change the original target instruction, then the host instructions are no longer valid. Consequently, the emulator must constantly check to determine whether a store is to the target code area. All of these problems make this type of emulation much slower than running a target application on a target processor.

Another example of the type of emulation software shown in figure 1(b) is described in an article entitled, "Talisman: Fast and Accurate Multicomputer Simulation," R. C. Bedichek, Laboratory for Computer Sciences, Massachusetts Institute of Technology. This is a more
5 complete example of translation in that it can emulate a complete research system and run the research target operating system. Talisman uses a host UNIX operating system.

In Figure 1(c), another example of emulation is shown. In this case, a PowerPC microprocessor used in an Apple Macintosh computer is
10 represented running a target application program which was designed to be run on the Motorola 68000 family CISC processors used in the original Macintosh computers; this type of arrangement has been required in order to allow Apple legacy programs to run on the Macintosh computers with RISC processors. As may be seen, the
15 target application is run on the host processor using at least a partial target operating system to respond to the application-like portions of the target operating system. A software emulator breaks the instructions furnished by the target application program and the application-like target operating system programs into instructions
20 which the host processor and its host operating system are capable of executing. The host operating system provides the interfaces through which access to the memory and input/output hardware of the host computer may be gained.

Again, the host RISC processor and the devices associated with it in
25 the host RISC computer are quite different than are the devices associated with the Motorola CISC processor; and the various target instructions are designed to cooperate with the target CISC operating system in accessing the various portions of the target computer.

Consequently, the emulation program must link the operations designed to operate hardware devices in the target computer to operations which hardware devices of the host system are capable of implementing. This requires the emulator to create software virtual
5 devices which respond to the instructions of the target application and to create links from these virtual devices through the host operating system to host hardware devices which are present but are addressed in a different manner by the host operating system.

The target software run in this manner runs relatively slowly for the
10 same reasons that the emulation of Figure 1(b) runs slowly. First, each target instruction from the target application and from the target operating system must be changed by fetching the instruction; and all of the host primitive functions derived from that instruction must be run in sequence each time the instruction is executed. Second, the
15 emulation software must generate virtual devices for each of the target application calls to the host operating system; and each of these virtual devices must provide calls to the actual host devices. Third, the emulator must treat all instructions as conservatively as it treats instructions which are directed to memory mapped I/O devices or risk
20 generating exceptions from which it cannot recover. Finally, the emulator must maintain the correct target state at all times and store operations must always check ahead to determine whether a store is to the target code area. All of these requirements eliminate the ability of the emulator to practice significant optimization of the code run on
25 the host processor and make this type of emulation much slower than running the target application on a target processor. Emulation rates less than one-quarter as fast as state of the art processors are considered very good. In general, this has relegated this type of

emulation software to uses where the capability of running applications designed for another processor is useful but not primary.

In Figure 1(d), a particular method of emulating a target application program on a host processor which provides relatively good

5 performance for a very limited series of target applications is illustrated. The target application furnishes instructions to an emulator which changes those instructions into instructions for the host processor and the host operating system. The host processor is a Digital Equipment Corporation Alpha RISC processor, and the host
10 operating system is Microsoft NT. The only target applications which may be run by this system are 32 bit applications designed to be executed by a target X86 processor with a Windows WIN32s compliant operating system. Since the host and target operating systems are almost identical, being designed to handle these same instructions,
15 the emulator software may change the instructions very easily. Moreover, the host operating system is already designed to respond to the same calls that the target application generates so that the generation of virtual devices is considerably reduced.

Although this is technically an emulation system running a target
20 application on a host processor, it is a very special case. Here the emulation software is running on a host operating system already designed to run similar applications. This allows the calls from the target applications to be more simply directed to the correct facilities of the host and the host operating system. More importantly, this
25 system will run only 32 bit Windows applications which probably amount to less than one percent of all X86 applications. Moreover, this system will run applications on only one operating system, Windows NT; while X86 processors run applications designed for a

large number of operating systems. Such a system, therefore, could be considered not to be compatible within the terms expressed earlier in this specification. Thus, a processor running such an emulator cannot be considered to be a competitive X86 processor.

5 Another method of emulation by which software may be used to run portions of applications written for a first instruction set on a computer which recognizes a different instruction set is illustrated in Figure 1(e). This form of emulation software is typically utilized by a programmer who may be porting an application from one computer
10 system to another. Typically, the target application is being designed for some target computer other than the host machine on which the emulator is being run. The emulator software analyzes the target instructions, translates those instructions into instructions which may be run on the host machine, and caches those host instructions
15 so that they may be reused. This dynamic translation and caching allows portions of applications to be run very rapidly. This form of emulator is normally used with software tracing tools to provide detailed information about the behavior of a target program being run. The output of a tracing tool may, in turn, be used to drive an analyzer
20 program which analyzes the trace information.

In order to determine how the code actually functions, an emulator of this type, among other things, runs with the host operating system on the host machine, furnishes the virtual hardware which the host operating system does not provide, and otherwise maps the operations
25 of the computer for which the application was designed to the hardware resources of the host machine in order to carry out the operations of the program being run. This software virtualizing of

hardware and mapping to the host computer can be very slow and incomplete.

Moreover, because it often requires a plurality of host instructions to carry out one of the target instructions, exceptions including faults and traps which require a target operating system exception handler may be generated and cause the host to cease processing the host instructions at a point unrelated to target instruction boundaries. When this happens, it may be impossible to handle the exception correctly because the state of the host processor and memory is incorrect. If this is the case, the emulator must be stopped and rerun to trace the operations which generated the exception. Thus, even though such an emulator may run sequences of target code very rapidly, it has no method for recovering from these exceptions so cannot run any significant portion of an application rapidly.

This is not a particular problem with this form of emulator because the functions being performed by the emulators, tracers, and the associated analyzers are directed to generating new programs or porting old programs to another machine so that the speed at which the emulator software runs is rarely at issue. That is, a programmer is usually not interested in how fast the code produced by a emulator runs on the host machine but in whether the emulator produces code which is executable on the machine for which it is designed and which will run rapidly on that machine. Consequently, this type of emulation software does not provide a method for running application programs written in a first instruction set to run on a different type of microprocessor for other than programming purposes. An example of this type of emulation software is described in an article entitled,

"Shade: A Fast Instruction-Set Simulator for Execution Profiling,"
Cmelik and Keppel.

It is desirable to provide competitive microprocessors which are faster
and less expensive than state of the art microprocessors yet are
5 entirely compatible with target application programs designed for state
of the art microprocessors running any operating systems available for
those microprocessors.

Summary Of The Invention

It is, therefore, an object of the present invention to provide a
10 microprocessor which is less expensive than conventional state of the
art microprocessors yet is compatible with and capable of running
application programs and operating systems designed for other
microprocessors at a faster rate than those other microprocessors.

This and other objects of the present invention are realized by a
15 microprocessor for a host computer designed to execute target
programs for a target computer having a target instruction set
comprising the combination of software, and enhanced host
processing hardware designed to execute instructions of a host
instruction set, the combination of the software and the enhanced
20 host processing hardware comprising means to translate a set of
target instructions into instructions of a host instruction set.

In a preferred embodiment, the combination of the software and the
enhanced host processing hardware includes means to optimize the
instructions of the host instruction set translated from the target
25 program speculating upon the occurrence of a condition, means to
determine under control of the software official state of the target

computer which existed at the beginning of a translation of a set of target instructions during execution of the target program by the microprocessor, means for updating state of the target computer from state of the host computer when a set of host instructions executes in accordance with the speculation, means to detect failure of the condition during the execution of the set of host instructions, means for updating state of the host computer from state of the target computer when a set of host instructions fails to execute in accordance with the speculation, and means to translate a new set of host instructions without the speculation when a set of host instructions fails to execute in accordance with the speculation.

In a preferred embodiment, the enhanced processing hardware of the morph host includes a very long instruction word (VLIW) processor designed to allow a number of instructions of the target instruction set to be translated, optimized, reordered, and rescheduled into very long instruction words which may be cached for later reuse thereby increasing the speed of execution by eliminating the need for each of these steps each time the target instruction is encountered. This allows the primitive instructions of the host instruction set which have been generated from a number of instructions of the target instruction set to be reordered and scheduled together to effect advanced superscalar operations and other time-saving operations which eliminate unnecessary hardware operations and accelerate overall operation.

These and other objects and features of the invention will be better understood by reference to the detailed description which follows taken together with the drawings in which like elements are referred to by like designations throughout the several views.

Brief Description Of The Drawings

Figures 1(a)-(e) are diagrams illustrating the manner of operation of microprocessors designed in accordance with the prior art.

5 Figure 2 is a block diagram of a microprocessor designed in accordance with the present invention running an application designed for a different microprocessor.

Figure 3 is a diagram illustrating a portion of the microprocessor shown in Figure 2.

10 Figure 4 is a block diagram illustrating a register file used in a microprocessor designed in accordance with the present invention.

Figure 5 is a block diagram illustrating a gated store buffer designed in accordance with the present invention.

15 Figure 6(a)-(c) illustrate instructions used in various microprocessors of the prior art and in a microprocessor designed in accordance with the present invention.

Figure 7 illustrates a method practiced by a software portion of a microprocessor designed in accordance with the present invention.

Figure 8 illustrates another method practiced by a software portion of a microprocessor designed in accordance with the present invention.

20 Figure 9 is a block diagram illustrating an improved computer system including the present invention.

Figure 10 is a block diagram illustrating a portion of the microprocessor shown in Figure 2.

Notation And Nomenclature

Some portions of the detailed descriptions which follow are presented in terms of symbolic representations of operations on data bits within a computer memory. These descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. The operations are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities.

Further, the manipulations performed are often referred to in terms, such as adding or comparing, which are commonly associated with mental operations performed by a human operator. No such capability of a human operator is necessary or desirable in most cases in any of the operations described herein which form part of the present invention; the operations are machine operations. Useful machines for performing the operations of the present invention include general purpose digital computers or other similar devices. In all cases the distinction between the method operations in operating a computer and the method of computation itself should be borne in mind. The present invention relates to a method and apparatus for operating a computer in processing electrical or other (e.g.

mechanical, chemical) physical signals to generate other desired physical signals.

During the following description, in some cases the target program is referred to as a program which is designed to be executed on an X86 microprocessor in order to provide exemplary details of operation because the majority of emulators run X86 applications. However, the target program may be one designed to run on any family of target computers. This includes target virtual computers, such as Pcode machines, Postscript machines, or Java virtual machines.

10 Detailed Description

The present invention overcomes the problems of the prior art and provides a microprocessor which is faster than microprocessors of the prior art, is capable of running all of the software for all of the operating systems which may be run by a large number of families of prior art microprocessors, yet is less expensive than prior art microprocessors.

Rather than using a microprocessor with more complicated hardware to accelerate its operation, the present invention combines an enhanced hardware processing portion (referred to as a "morph host" in this specification) which is much simpler than state of the art microprocessors and an emulating software portion (referred to as "code morphing software" in this specification) in a manner that the two portions function together as a microprocessor with more capabilities than any known competitive microprocessor. More particularly, a morph host is a processor which includes hardware enhancements to assist in having state of a target computer immediately at hand when an exception or error occurs, while code

morphing software is software which translates the instructions of a target program to morph host instructions for the morph host and responds to exceptions and errors by replacing working state with correct target state when necessary so that correct retranslations occur. Code morphing software may also include various processes for enhancing the speed of processing. Rather than providing hardware to enhance the speed of processing as do all of the very fast prior art microprocessors, the present invention allows a large number of acceleration enhancement techniques to be carried out in selectable stages by the code morphing software. Providing the speed enhancement techniques in the code morphing software allows the morph host to be implemented using much less complicated hardware which is faster and substantially less expensive than the hardware of prior art microprocessors. As a comparison, one embodiment of the present invention designed to run all available X86 applications is implemented by a morph host including approximately one-quarter of the number of gates of the Pentium Pro microprocessor yet runs X86 applications substantially faster than does the Pentium Pro microprocessor or any other known microprocessor capable of processing these applications.

The code morphing software utilizes certain techniques which have previously been used only by programmers designing new software or emulating new hardware. The morph host includes hardware enhancements especially adapted to allow the acceleration techniques provided by the code morphing software to be utilized efficiently. These hardware enhancements allow the code morphing software to implement acceleration techniques over a broader range of instructions. These hardware enhancements also permit additional

acceleration techniques to be practiced by the code morphing software which are unavailable in hardware processors and could not be implemented in those processors except at exorbitant cost. These techniques significantly increase the speed of the microprocessor of the present invention compared to the speeds of prior art microprocessors practicing the execution of native instruction sets.

For example, the code morphing software combined with the enhanced morph host allows the use of techniques which allow the reordering and rescheduling of primitive instructions generated by a sequence of target instructions without requiring the addition of significant circuitry. By allowing the reordering and rescheduling of a number of target instructions together, other optimization techniques can be used to reduce the number of processor steps which are necessary to carry out a group of target instructions to fewer than those required by any other microprocessors which will run the target applications.

The code morphing software combined with the enhanced morph host translates target instructions into instructions for the morph host on the fly and caches those host instructions in a memory data structure (referred to in this specification as a "translation buffer"). The use of a translation buffer to hold translated instructions allows instructions to be recalled without rerunning the lengthy process of determining which primitive instructions are required to implement each target instruction, addressing each primitive instruction, fetching each primitive instruction, optimizing the sequence of primitive instructions, allocating assets to each primitive instruction, reordering the primitive instructions, and executing each step of each sequence of primitive instructions involved each time each target instruction is

executed. Once a target instruction has been translated, it may be recalled from the translation buffer and executed without the need for any of these myriad of steps.

A primary problem of prior art emulation techniques has been the inability of these techniques to handle with good performance exceptions generated during the execution of a target program. This is especially true of exceptions generated in running the target application which are directed to the target operating system where the correct target state must be available at the time of any such exception for proper execution of the exception and the instructions which follow. Consequently, the emulator is forced to keep accurate track of the target state at all times and must constantly check to determine whether a store is to the target code area. Other exceptions create similar problems. For example, exceptions can be generated by the emulator to detect particular target operations which have been replaced by some particular host function. In particular, various hardware operations of a target processor may be replaced by software operations provided by the emulator software. Additionally, the host processor executing the host instructions derived from the target instructions can also generate exceptions. All of these exceptions can occur either during the attempt to change target instructions into host instructions by the emulator, or when the host translations are executed on the host processor. An efficient emulation must provide some manner of recovering from these exceptions efficiently and in a manner that the exception may be correctly handled. None of the prior art does this for all software which might be emulated.

In order to overcome these limitations of the prior art, the present invention incorporates a number of hardware improvements in its

enhanced morph host. These improvements include a gated store buffer and a large plurality of additional processor registers. Some of the additional registers allow the use of register renaming to lessen the problem of instructions needing the same hardware resources.

5 The additional registers also allow the maintenance of a set of host or working registers for processing the host instructions and a set of target registers to hold the official state of the target processor for which the target application was created. The target (or shadow) registers are connected to their working register equivalents through a

10 dedicated interface that allows an operation called "commit" to quickly transfer the content of all working registers to official target registers and allows an operation called "rollback" to quickly transfer the content of all official target registers back to their working register equivalents. The gated store buffer stores working memory state

15 changes on an "uncommitted" side of a hardware "gate" and official memory state changes on a "committed" side of the hardware gate where these committed stores "drain" to main memory. A commit operation transfers stores from the uncommitted side of the gate to the committed side of the gate. The additional official registers and

20 the gated store buffer allow the state of memory and the state of the target registers to be updated together once one or a group of target instructions have been translated and run without error.

These updates are chosen by the code morphing software to occur on integral target instruction boundaries. Thus, if the primitive host

25 instructions making up a translation of a series of target instructions are run by the host processor without generating exceptions, then the working memory stores and working register state generated by those instructions are transferred to official memory and to the official target

registers. In this manner, if an exception occurs when processing the host instructions at a point which is not on the boundary of one or a set of target instructions being translated, the original state in the target registers at the last update (or commit) may be recalled to the working registers and uncommitted memory stores in the gated store buffer may be dumped. Then, for the case where the exception generated is a target exception, the target instructions causing the target exception may be retranslated one at a time and executed in serial sequence as they would be executed by a target microprocessor.

As each target instruction is correctly executed without error, the state of the target registers may be updated; and the data in the store buffer gated to memory. Then, when the exception occurs again in running the host instructions, the correct state of the target computer is held by the target registers of the morph host and memory; and the operation may be correctly handled without delay. Each new translation generated by this corrective translating may be cached for future use as it is translated or alternatively dumped for a one time or rare occurrence such as a page fault. This allows the microprocessor created by the combination of the code morphing software and the morph host to execute the instructions more rapidly than processors for which the software was originally written.

It should be noted that in executing target programs using the microprocessor of the present invention, many different types of exceptions can occur which are handled in different manners. For example, some exceptions are caused by the target software generating an exception which utilizes a target operating system exception handler. The use of such an exception handler requires that the code morphing software include routines for emulating the

entire exception handling process including any hardware provided by the target computer for handling the process. This requires that the code morphing software provide for saving the state of the target processor so that it may proceed correctly after the exception has been handled. Some exceptions like a page fault, which requires fetching data in a new page of memory before the process being translated may be implemented, require a return to the beginning of the process being translated after the exception has been handled. Other exceptions implement a particular operation in software where that operation is not provided by the hardware. These require that the exception handler return the operation to the next step in the translation after the exception has been handled. Each of these different types of exceptions may be efficiently handled by the present invention.

Additionally, some exceptions are generated by host hardware and detect a variety of host and target conditions. Some exceptions behave like exceptions on a conventional microprocessor, but others are used by the code morphing software to detect failure of various speculations. In these cases, the code morphing software, using the state saving and restoring mechanisms described above, causes the target state to be restored to its most recent official version and generates and saves a new translation (or re-uses a previously generated safe translation) which avoids the failed speculation. This translation is then executed.

The morph host includes additional hardware exception detection mechanisms that in conjunction with the rollback and retranslate method described above allow further optimization. Examples are a means to distinguish memory from memory mapped I/O and a means

to eliminate memory references by protecting addresses or address ranges thus allowing target variables to be kept in registers.

For the case where exceptions are used to detect failure of other speculations, such as whether an operation affects memory or memory mapped I/O, recovery is accomplished by the generation of
5 new translations with different memory operations and different optimizations.

Figure 2 is a diagram of morph host hardware designed in accordance with the present invention represented running the same application
10 program which is being run on the CISC processor of Figure 1(a). As may be seen, the microprocessor includes the code morphing software portion and the enhanced hardware morph host portion described above. The target application furnishes the target instructions to the code morphing software for translation into host instructions which
15 the morph host is capable of executing. In the meantime, the target operating system receives calls from the target application program and transfers these to the code morphing software. In a preferred embodiment of the invention, the morph host is a very long instruction word (VLIW) processor which is designed with a plurality
20 of processing channels. The overall operation of such a processor is further illustrated in Figure 6(c).

In Figure 6(a)-(c) are illustrated instructions adapted for use with each of a CISC processor, a RISC processor, and a VLIW processor. As may be seen, the CISC instructions are of varied lengths and may include a
25 plurality of more primitive operations (e.g., load and add). The RISC instructions, on the other hand, are of equal length and are essentially primitive operations. The single very long instruction for the VLIW

processor illustrated includes each of the more primitive operations (i.e., load, store, integer add, compare, floating point multiply, and branch) of the CISC and RISC instructions. As may be seen in Figure 6(c), each of the primitive instructions which together make up a
5 single very long instruction word is furnished in parallel with the other primitive instructions either to one of a plurality of separate processing channels of the VLIW processor or to memory to be dealt with in parallel by the processing channels and memory. The results of all of these parallel operations are transferred into a multiported
10 register file.

A VLIW processor which may be the basis of the morph host is a much simpler processor than the other processors described above. It does not include circuitry to detect issue dependencies or to reorder, optimize, and reschedule primitive instructions. This, in turn, allows
15 faster processing at higher clock rates than is possible with either the processors for which the target application programs were originally designed or other processors using emulation programs to run target application programs. However, the invention is not limited to VLIW processors and may function as well with any type of processor such
20 as a RISC processor.

The code morphing software of the microprocessor shown in Figure 2 includes a translator portion which decodes the instructions of the target application, converts those target instructions to the primitive host instructions capable of execution by the morph host, optimizes
25 the operations required by the target instructions, reorders and schedules the primitive instructions into VLIW instructions (a translation) for the morph host, and executes the host VLIW instructions. The operations of the translator are illustrated in Figure

7 which illustrates the operation of the main loop of the code morphing software.

In order to accelerate the operation of the microprocessor which includes the code morphing software and the enhanced morph host hardware, the code morphing software includes a translation buffer as
5 is illustrated in Figure 2. The translation buffer of one embodiment is a software data structure which may be stored in memory; a hardware cache might also be utilized in a particular embodiment. The translation buffer is used to store the host instructions which embody
10 each completed translation of the target instructions. As may be seen, once the individual target instructions have been translated and the resulting host instructions have been optimized, reordered, and rescheduled, the resulting host translation is stored in the translation buffer. The host instructions which make up the translation are then
15 executed by the morph host. If the host instructions are executed without generating an exception, the translation may thereafter be recalled whenever the operations required by the target instruction or instructions are required.

Thus, as shown in Figure 7, a typical operation of the code morphing
20 software of the microprocessor when furnished the address of a target instruction by the application program is to first determine whether the target instruction at the target address has been translated. If the target instruction has not been translated, it and subsequent target instructions are fetched, decoded, translated, and then (possibly)
25 optimized, reordered, and rescheduled into a new host translation, and stored in the translation buffer by the translator. As will be seen later, there are various degrees of optimization which are possible. The term "optimization" is often used generically in this specification

to refer to those techniques by which processing is accelerated. For example, reordering is one form of optimization which allows faster processing and which is included within the term. Many of the optimizations which are possible have been described within the prior art of compiler optimizations, and some optimizations, which were
5 difficult to perform within the prior art like "super-blocks" come from VLIW research. Control is then transferred to the translation to cause execution by the enhanced morph host hardware to resume.

When the particular target instruction sequence is next encountered
10 in running the application, the host translation will then be found in the translation buffer and immediately executed without the necessity of translating, optimizing, reordering, or rescheduling. Using the advanced techniques described below, it has been estimated that the translation for a target instruction (once completely translated) will be
15 found in the translation buffer all but once for each one million or so executions of the translation. Consequently, after a first translation, all of the steps required for translation such as decoding, fetching primitive instructions, optimizing the primitive instructions, rescheduling into a host translation, and storing in the translation
20 buffer may be eliminated from the processing required. Since the processor for which the target instructions were written must decode, fetch, reorder, and reschedule each instruction each time the instruction is executed, this drastically reduces the work required for executing the target instructions and increases the speed of the
25 microprocessor of the present invention.

In eliminating all of these steps required in execution of a target application by prior art processors, the microprocessor of the present invention overcomes problems of the prior art which made the

operations of the present invention impossible at any reasonable speed. For example, some of the techniques of the present invention were used in the emulators described above used for porting applications to other systems. However, some of these emulators had
5 no way of running more than short portions of applications because in processing translated instructions, exceptions which generate calls to various system exception handlers were generated at points in the operation at which the state of the host processor had no relation to the state of a target processor processing the same instructions.
10 Because of this, the state of the target processor at the point at which such an exception was generated was not known. Thus, correct state of the target machine could not be determined; and the operation would have to be stopped, restarted, and the correct state ascertained before the exception could be serviced and execution continued. This
15 made running an application program at host speed impossible.

The morph host hardware of the present invention includes a number of enhancements which overcome this problem. These enhancements are each illustrated in Figures 3, 4, and 5. In order to determine the correct state of the registers at the time an error occurs, a set of
20 official target registers is provided by the enhanced hardware to hold the state of the registers of the target processor for which the original application was designed. These target registers may be included in each of the floating point units, any integer units, and any other execution units. These official registers have been added to the morph
25 host of the present invention along with an increased number of normal working registers so that a number of optimizations including register renaming may be practiced. One embodiment of the enhanced hardware includes sixty-four working registers in the

integer unit and thirty-two working registers in the floating point unit. The embodiment also includes an enhanced set of target registers which include all of the frequently changed registers of the target processor necessary to provide the state of that processor ; these
5 include condition control registers and other registers necessary for control of the simulated system.

It should be noted that depending on the type of enhanced processing hardware utilized by the morph host, a translated instruction sequence may include primitive operations which constitute a
10 plurality of target instructions from the original application. For example, a VLIW microprocessor may be capable of running a plurality of either CISC or RISC instructions at once as is illustrated in Figure 6(a)-(c). Whatever the morph host type, the state of the target registers of the morph host hardware of the invention is not
15 changed except at an integral target instruction boundary; and then all target registers are updated. Thus, if the microprocessor of the present invention is executing a target instruction or instructions which have been translated into a series of primitive instructions which may have been reordered and rescheduled into a host
20 translation, when the processor begins executing the translated instruction sequence, the official target registers hold the values which would be held by the registers of the target processor for which the application was designed when the first target instruction was addressed. After the morph host has begun executing the translated
25 instructions, however, the working registers hold values determined by the primitive operations of the translated instructions executed to that point. Thus, while some of these working registers may hold values which are identical to those in the official target registers,

others of the working registers hold values which are meaningless to the target processor. This is especially true in an embodiment which provides many more registers than does a particular target machine in order to allow advanced acceleration techniques. Once the translated
5 host instructions begin, the values in the working registers are whatever those translated host instructions determine the condition of those registers to be. If a set of translated host instructions is executed without generating an exception, then the new working register values determined at the end of the set of instructions are
10 transferred together to the official target registers (possibly including a target instruction pointer register). In the present embodiment of the invention, this transfer occurs outside of the execution of the host instructions in an additional pipeline stage so it does not slow operation of the morph host.

15 In a similar manner, a gated store buffer such as that illustrated in Figure 5 is utilized in the present invention to control the transfer of data to memory. The gated store buffer includes a number of elements each of which may hold the address and data for a memory store operation. These elements may be implemented by any of a
20 number of different hardware arrangements (e.g., first-in first-out buffers); the embodiment illustrated is implemented utilizing random access memory and three dedicated working registers. The three registers store, respectively, a pointer to the head of the queue of memory stores, a pointer to the gate, and a pointer to the tail of the
25 queue of the memory stores. Memory stores positioned between the head of the queue and the gate are already committed to memory, while those positioned between the gate of the queue and the tail are not yet committed to memory. Memory stores generated during

execution of host translations are placed in the store buffer by the integer unit in the order generated during the execution of the host instructions by the morph host but are not allowed to be written to memory until a commit operation is encountered in a host instruction.

5 Thus, as translations execute, the store operations are placed in the queue. Assuming these are the first stores so that no other stores are in the gated store buffer, both the head and gate pointers will point to the same position. As each store is executed, it is placed in the next position in the queue and the tail point is incremented to the next
10 position (upward in the figure). This continues until a commit command is executed. This will normally happen when the translation of a set of target instructions has been completed without generating an exception or a error exit condition. When a translation has been executed by the morph host without error, then the memory
15 stores in the store buffer generated during execution are moved together past the gate of the store buffer (committed) and subsequently written to memory. In the embodiment illustrated, this is accomplished by copying the value in the register holding the tail pointer to the register holding the gate pointer.

20 Thus, it may be seen that both the transfer of register state from working registers to official target registers and the transfer of working memory stores to official memory occur together and only on boundaries between integral target instructions in response to explicit commit operations.

25 This allows the microprocessor to recover from target exceptions which occur during execution by the enhanced morph host without any significant delay. If a target exception is generated during the running of any translated instruction or instructions, that exception is

detected by the morph host hardware or software. In response to the detection of the target exception, the code morphing software may cause the values retained in the official registers to be placed back into the working registers and any non-committed memory stores in
5 the gated store buffer to be dumped (an operation referred to as "rollback"). The memory stores in the gated store buffer of Figure 5 may be dumped by copying the value in the register holding the gate pointer to the register holding the tail pointer.

Placing the values from the target registers into the working registers
10 may place the address of the first of the target instructions which were running when the exception occurred in the working instruction pointer register. Beginning with this official state of the target processor in the working registers, the target instructions which were running when the exception occurred are retranslated in serial order
15 without any reordering or other optimizing. After each target instruction is newly decoded and translated into a new host translation, the translated host instruction representing the target instructions is executed by the morph host and causes or does not cause an exception to occur. (If the morph host is other than a VLIW
20 processor, then each of the primitive operations of the host translation is executed in sequence. If no exception occurs as the host translation is run, the next primitive function is run.) This continues until an exception re-occurs or the single target instruction has been translated and executed. In one embodiment, if a translation of a
25 target instruction is executed without an exception being generated, then the state of working registers is transferred to the target registers and any data in the gated store buffer is committed so that it may be transferred to memory. However, if an exception re-occurs during the

running of a translation, then the state of the target registers and memory has not changed but is identical to the state produced in a target computer when the exception occurs. Consequently, when the target exception is generated, the exception will be correctly handled by the target operating system.

Similarly, once a first target instruction of the series of instructions the translation of which generated an exception has been executed without generating an exception, the target instruction pointer points to the next of the target instructions. This second target instruction is decoded and retranslated without optimizing or reordering in the same manner as the first. As each of the host translations of a single target instruction is processed by the morph host, any exception generated will occur when the state of the target registers and memory is identical to the state which would occur in the target computer. Consequently, the exception may be immediately and correctly handled. These new translations may be stored in the translation buffer as the correct translations for that sequence of instructions in the target application and recalled whenever the instructions are rerun.

Other embodiments of the invention for accomplishing the same result as the gated store buffer of Figure 5 might include arrangements for transferring stores directly to memory while recording data sufficient to recover state of the target computer in case the execution of a translation results in an exception or an error necessitating rollback. In such a case, the effect of any memory stores which occurred during translation and execution would have to be reversed and the memory state existing at the beginning of the translation restored; while working registers would have to receive data held in the official target

registers in the manner discussed above. One embodiment for accomplishing this maintains a separate target memory to hold the original memory state which is then utilized to replace overwritten memory if a rollback occurs. Another embodiment for accomplishing
5 memory rollback logs each store and the memory data replaced as they occur, and then reverses the store process if rollback is required.

The code morphing software of the present invention provides an additional operation which greatly enhances the speed of processing programs which are being translated. In addition to simply
10 translating the instructions, optimizing, reordering, rescheduling, caching, and executing each translation so that it may be rerun whenever that set of instructions needs to be executed, the translator also links the different translations to eliminate in almost all cases a return to the main loop of the translation process. Figure 8 illustrates
15 the steps carried out by the translator portion of the code morphing software in accomplishing this linking process. It will be understood by those skilled in the art that this linking operation essentially eliminates the return to the main loop for most translations of instructions, which eliminates this overhead.

20 Presume for exemplary purposes that the target program being run consists of X86 instructions. When a translation of a sequence of target instructions occurs and the primitive host instructions are reordered and rescheduled, two primitive instructions may occur at the end of each host translation. The first is a primitive instruction
25 which updates the value of the instruction pointer for the target processor (or its equivalent); this instruction is used to place the correct address of the next target instruction in the target instruction pointer register. Following this primitive instruction is a branch

instruction which contains the address of each of two possible targets for the branch. The manner in which the primitive instruction which precedes the branch instruction may update the value of the instruction pointer for the target processor is to test the condition
5 code for the branch in the condition code registers and then determine whether one of the two branch addresses indicated by the condition controlling the branch is stored in the translation buffer. The first time the sequence of target instructions is translated, the two branch targets of the host instruction both hold the same host processor
10 address for the main loop of the translator software.

When the host translation is completed, stored in the translation buffer, and executed for the first time, the instruction pointer is updated in the target instruction pointer register (as are the rest of the target registers); and the operation branches back to the main loop.
15 At the main loop, the translator software looks up the instruction pointer to the next target instruction in the target instruction pointer register. Then the next target instruction sequence is addressed. Presuming that this sequence of target instructions has not yet been translated and therefore a translation does not reside in the
20 translation buffer, the next set of target instructions is fetched from memory, decoded, translated, optimized, reordered, rescheduled, cached in the translation buffer, and executed. Since the second set of target instructions follows the first set of target instructions, the primitive branch instruction at the end of the host translation of the
25 first set of target instructions is automatically updated to substitute the address of the host translation of the second set of target instructions as the branch address for the particular condition controlling the branch.

If then, the second translated host instruction were to loop back to the first translated host instruction, the branch operation at the end of the second translation would include the main loop address and the X86 address of the first translation as the two possible targets for the branch. The update-instruction-pointer primitive operation preceding the branch tests the condition and determines that the loop back to the first translation is to be taken and updates the target instruction pointer to the X86 address of the first translation. This causes the translator to look in the translation buffer to see if the X86 address being sought appears there. The address of the first translation is found, and its value in host memory space is substituted for the X86 address in the branch at the end of the second host translated instruction. Then, the second host translated instruction is cached and executed. This causes the loop to be run until the condition causing the branch from the first translation to the second translation fails, and the branch takes the path back to the main loop. When this happens, the first translated host instruction branches back to the main loop where the next set of target instructions designated by the target instruction pointer is searched for in the translation buffer, the host translation is fetched from the cache; or the search in the translation buffer fails, and the target instructions are fetched from memory and translated. When this translated host instruction is cached in the translation buffer, its address replaces the main loop address in the branch instruction which ended the loop.

In this manner, the various translated host instructions are chained to one another so that the need to follow the long path through the translator main loop only occurs where a link does not exist. Eventually, the main loop references in the branch instructions of

host instructions are almost completely eliminated. When this condition is reached, the time required to fetch target instructions, decode target instructions, fetch the primitive instructions which make up the target instructions, optimize those primitive operations, reorder the primitive operations, and reschedule those primitive operations before running any host instruction is eliminated. Thus, in contrast to all prior art microprocessors which must take each of these steps each time any application instruction sequence is run, the work required to run any set of target instructions using the present invention after the first translation has taken place is drastically reduced. This work is further reduced as each set of translated host instructions is linked to the other sets of translated host instructions. In fact, it is estimated that translation will be needed in less than one translation execution out of one million during the running of an application.

Those skilled in the art will recognize that the implementation of the present invention requires a large translation buffer since each set of instructions which is translated is cached in order that it need not be translated again. Translators designed to function with applications programmed for different systems will vary in their need for supporting buffer memory. However, one embodiment of the invention designed to run X86 programs utilizes a translation buffer of two megabytes of random access memory.

Two additional hardware enhancements help to increase the speed at which applications can be processed by the microprocessor of the present invention. The first of these is an abnormal/normal (A/N) protection bit stored with each address translation in a translation look-aside buffer (TLB) (see Figure 3) where lookup of the physical

address of target instructions is first accomplished. Target memory operations within translations can be of two types, ones which operate on memory (normal) or ones which operate on a memory mapped I/O device (abnormal).

5 A normal access which affects memory completes normally. When instructions operate on memory, the optimizing and reordering of those instructions is appropriate and greatly aids in speeding the operation of any system using the microprocessor of the present invention. On the other hand, the operations of an abnormal access
10 which affects an I/O device often must be practiced in the precise order in which those operations are programmed without the elimination of any steps or they may have some adverse affect at the I/O device. For example, a particular I/O operation may have the effect of clearing an I/O register; if the primitive operations take place
15 out of order, then the result of the operations may be different than the operation commanded by the target instruction. Without a means to distinguish memory from memory mapped I/O, it is necessary to treat all memory with the conservative assumptions used to translate instruction which affect memory mapped I/O. This severely restricts
20 the nature of optimizations that are achievable. Because prior art emulators lacked means to both detect a failure of speculation on the nature of the memory being addressed, and means to recover from such failures, their performance was restricted.

In one embodiment of the invention, the A/N bit is initially set in the
25 translation look-aside buffer to indicate a memory page. A translation of an operation which affects memory as though it were a memory operation is actually a speculation that the operation is one affecting memory. After the translation has been accomplished and executes,

the target memory reference is checked by comparing the access type (normal, or abnormal) against the TLB A/N protection bit. When the access type does not match the A/N protection, an exception occurs. If the operation in fact affects memory, then the optimizing, 5 reordering, and rescheduling techniques described above were correctly applied. If the comparison of the A/N bit in the TLB shows that the operation, however, affects an I/O device, then execution causes an exception to be taken; and the translator produces a new translation one target instruction at a time without optimizing, 10 reordering, or rescheduling of any sort. Similarly, if a translation incorrectly assumes an I/O operation for an operation which actually affects memory, execution causes an exception to be taken; and the target instructions are retranslated using the optimizing, reordering, and rescheduling techniques. In this manner, the present invention 15 can enhance performance beyond what has been traditionally possible.

One of the most frequent speculations practiced by the present invention is that target exceptions will not occur within a translation. This allows significant optimization over the prior art. First, target 20 state does not have to be updated on each target instruction boundary, but only on target instruction boundaries which occur on translation boundaries. This eliminates instructions necessary to save target state on each target instruction boundary. Optimizations that would previously have been impossible in scheduling and 25 removing redundant operations are also made possible.

The present invention is admirably adapted to select the appropriate process of translation. In accordance with the method of translating described above, a set of instructions may first be translated as

though it were to affect memory. When the optimized, reordered, and rescheduled host instructions are then executed, the address may be found to refer to an I/O device by the condition of the A/N bit provided in the translation look-aside buffer. The comparison of the
5 A/N bit and the translated instruction address which shows that an operation is an I/O operation generates an error exception which causes a software initiated rollback procedure to occur, causing any uncommitted memory stores to be dumped and the values in the target registers to be placed back into the working registers. Then the
10 translation starts over, one target instruction at a time without optimization, reordering, or rescheduling. This re-translation is the appropriate host translation for an I/O device.

In a similar manner, it is possible for a memory operation to be incorrectly translated as an I/O operation. The error generated may
15 be used to cause its correct re-translation where it may be optimized, reordered, and rescheduled to provide faster operation.

Prior art emulators have also struggled with what is generally referred to as self modifying code. Should a target program write to the memory that contains target instructions, this will cause translations
20 that exist for these target instructions to become "stale" and no longer valid. It is necessary to detect these stores as they occur dynamically. In the prior art, such detection has to be accomplished with extra instructions for each store. This problem is larger in scope than programs modifying themselves. Any agent which can write to
25 memory, such as a second processor or a DMA device, can also cause this problem.

The present invention deals with this problem by another enhancement to the morph host. A translation bit (T bit) which may also be stored in the translation look-aside buffer is used to indicate target memory pages for which translations exist. The T bit thus possibly indicates that particular pages of target memory contain target instructions for which host translations exist which would become stale if those target instructions were to be overwritten. If an attempt is made to write to the protected pages in memory, the presence of the translation bit will cause an exception which when handled by the code morphing software can cause the appropriate translation(s) to be invalidated or removed from the translation buffer. The T bit can also be used to mark other target pages that translation may rely upon not being written.

This may be understood by referring to Figure 3 which illustrates in block diagram form the general functional elements of the microprocessor of the invention. When the morph host executes a target program, it actually runs the translator portion of the code morphing software which includes the only original untranslated host instructions which effectively run on the morph host. To the right in the figure is illustrated memory divided into a host portion including essentially the translator and the translation buffer and a target portion including the target instructions and data, including the target operating system. The morph host hardware begins executing the translator by fetching host instructions from memory and placing those instructions in an instruction cache. The translator instructions generate a fetch of the first target instructions stored in the target portion of memory. Carrying out a target fetch causes the integer unit to look to the official target instruction pointer register for

a first address of a target instruction. The first address is then accessed in the translation look-aside buffer of the memory management unit. The memory management unit includes hardware for paging and provides memory mapping facilities for the TLB.

5 Presuming that the TLB is correctly mapped so that it holds lookup data for the correct page of target memory, the target instruction pointer value is translated to the physical address of the target instruction. At this point, the condition of the bit (T bit) indicating whether a translation has been accomplished for the target
10 instruction is detected, but the access is a read operation and no T bit exception will occur. The condition of the A/N bit indicating whether the access is to memory or memory mapped I/O is also detected.

Presuming the last mentioned bit indicates a memory location, the target instruction is accessed in target memory since no translation
15 exists. The target instruction and subsequent target instructions are transferred as data to the morph host computing units and translated under control of the translator instructions stored in the instruction cache. The translator instructions utilize reordering, optimizing, and rescheduling techniques as though the target instruction affected
20 memory. The resulting translation containing a sequence of host instructions is then stored in the translation buffer in host memory.

The translation is transferred directly to the translation buffer in host memory via the gated store buffer. Once the translation has been stored in host memory, the translator branches to the translation
25 which then executes. The execution (and subsequent executions) will determine if the translation has made correct assumptions concerning exceptions and memory. Prior to executing the translation, the T bit for the target page(s) containing the target instructions that have been translated is set. This indication warns that the instruction has been

translated; and, if an attempt to write to the target address occurs, the attempt generates an exception which causes the translation to possibly be invalidated or removed.

5 An additional hardware enhancement to the morph host is a circuit utilized to allow data which is normally stored in memory but is used quite often in the execution of an operation to be replicated (or "aliased") in an execution unit register in order to eliminate the time required to fetch the data from memory on each use. To accomplish this in one embodiment, the morph host is designed to respond to a
10 "load and protect" command which copies the memory data to a working register 111 in an execution unit 110 shown in Figure 11 and places the memory address in a register 112 in that unit. Associated with the address register is a comparator 113. The comparator receives the addresses of loads and stores to the gated store buffer directed to memory during translations. If a memory address for
15 either a load or a store compares with an address in the register 112 (or additional registers depending on the implementation), an exception is generated. The code morphing software responds to the exception by assuring that the memory address and the register hold the same correct data. In one embodiment, this is accomplished by
20 rolling back the translation and reexecuting it without any "aliased" data in an execution register. Other possible methods of correcting the problem are to update the register with the latest memory data or memory with the latest load data.

25 It will be recognized by those skilled in the art that the host processor of the present invention may be connected in circuit with typical computer elements to form a computer such as that illustrated in Figure 9. As may be seen, when used in a modern X86 computer the

host processor is joined by a processor bus to memory and bus control circuitry. The memory and bus control circuitry is arranged to provide access to main memory as well as to cache memory which may be utilized with the microprocessor. The memory and bus control
5 circuitry also provides access to a bus such as a PCI or other local bus through which I/O devices may be accessed. The particular computer system will depend upon the circuitry utilized with a typical microprocessor which the microprocessor of the present invention replaces.

10 In order to illustrate the operation of the processor of the present invention and the manner in which acceleration of execution occurs, the translation of a small sample of X86 target code to host primitive instructions is presented at this point. The sample illustrates the translation of X86 target instructions to morph host instructions
15 including various exemplary steps of optimizing, reordering, and rescheduling by the microprocessor of the invention. By following the process illustrated, the substantial difference between the operations required to execute the original instructions using the target processor and the operations required to execute the translation on the host
20 processor will become apparent to those skilled in the art.

The original instruction illustrated in C language source code describes a very brief loop operation. Essentially, while some variable "n" which is being decremented after each loop remains greater than "0", a value "c" is stored at an address indicated by a pointer "*s"
25 which is being incremented after each loop.

Original C code

```
while( (n--)>0) {  
    *s++=c  
30 }
```

Win32 x86 instructions produced by a compiler compiling this C code.

```

5  mov    %ecx, [%ebp+0xc]    // load c from memory address into %ecx
   mov    %eax, [%ebp+0x8]    // load s from memory address into %eax
   mov    [%eax], %ecx        // store c into memory address s held in %eax
   add    %eax, #4            // increment s by 4
10  mov    [%ebp+0x8], %eax    // store (s + 4) back into memory
   mov    %eax, [%ebp+0x10]    // load n from memory address into %eax
   lea    %ecx, [%eax-1]      // decrement n and store result in %ecx
   mov    [%ebp+0x10], %ecx    // store (n-1) into memory
   and    %eax, %eax          // test n to set condition codes
15  jg     .-0x1b              // branch to top of this section if "n>0"

```

Notation: [...] indicates an address expression for a memory operand. In the example above, the address for a memory operand is formed from the contents of a register added to a hexadecimal constant indicated by the 0x prefix. Target registers are indicated with the % prefix, e.g. %ecx is the ecx register. The destination of an operation is to the left.

Target instruction key:

```

25  jg = jump if greater
    mov = move
    lea = load effective address
    and = AND

```

In this first portion of the sample, each of the individual X86 assembly language instructions for carrying out the execution of the operation defined by the C language statement is listed by the assembly language mnemonic for the operation followed by the parameters involved in the particular primitive operation. An explanation of the operation is also provided in a comment for each instruction. Even though the order of execution may be varied by the target processor from that shown, each of these assembly language instructions must be executed each time the loop is executed in carrying out the target C language instructions. Thus, if the loop is executed one hundred times, each instruction shown above must be carried out one hundred times.

Shows each X86 instruction shown above followed by the host instructions necessary to implement the X86 instruction.

```

    mov  %ecx, [% bp+0xc] // load c from memory address into ecx

    add  R0, Rbp, 0xc      ; form memory address and put it in R0
    ld   Recx, [R0]        ; load c from memory address in R0 into Recx
5
    mov  %eax, [%ebp+0x8] // load s from memory address into %eax

    add  R2, Rbp, 0x8      ; form memory address and put it in R2
    ld   Reax, [R2]        ; load s from memory address in R2 into Recx
10
    mov  [%eax], %ecx      // store c into memory address s held in %eax
    st   [Reax], Recx      ; store c into memory address s held in Reax

    add  %eax, #4          // increment s by 4
    add  Reax, Reax, 4      ; increment S by 4
15
    mov  [%ebp+0x8], %eax // store (s + 4) back into memory
20
    add  R5, Rbp, 0x8      ; form memory address and put it in R5
    st   [R5], Reax        ; store (s + 4) back into memory

    mov  %eax, [%ebp+0x10] // load n from memory address into %eax
25
    add  R7, Rbp, 0x10     ; form memory address and put it in R7
    ld   Reax, [R7]        ; load n from memory address into Reax

    lea  %ecx, [%eax-1]    // decrement n and store result in %ecx
30
    sub  Recx, Reax, 1      ; decrement n and store result in Recx

    mov  [%ebp+0x10], %ecx // store (n - 1) into memory

    add  R9, Rbp, 0x10     ; form memory address and put it in R9
    st   [R9], Recx        ; store (n - 1) into memory
35
    and  %eax, %eax        // test n to set condition codes

    andcc R11, Reax, Reax  ; test n to set condition codes
40
    jg   .-0x1b            // branch to top of this section if "n>0"

    jg   mainloop, mainloop ; jump to main loop
45
Host Instruction key:
    ld = load          add = ADD          st = store
    sub = subtract     jg = jump if condition codes indicate greater
    andcc = and set the condition codes

```

The next sample illustrates the same target primitive instructions which carry out the C language instructions. However, following each primitive target instruction are listed primitive host instructions required to accomplish the same operation in one particular embodiment of the microprocessor of the invention in which the morph host is a VLIW processor designed in the manner described herein. It should be noted that the host registers which are shadowed by official target registers are designated by an "R" followed by the X86 register designation so that, for example, Reax is the working register associated with the EAX official target register.

Adds host instructions necessary to perform X86 address computation and upper and lower segment limit checks.

```

15  mov  %ecx, [%ebp+0xc] // load c
    add  R0,Rebp,0xc      ; form logical address into R0
    chkl R0,Rss_limit     ; Check logical address against segment lower
                           limit
    chku R0,R_FFFFFFFF    ; Check logical address against segment upper
                           limit
20  add  R1,R0,Rss_base   ; add segment base to form linear address
    ld   Recx,[R1]        ; load c from memory address in R1 into Recx

    mov  %eax, [%ebp+0x8] // load s
25  add  R2,Rebp,0x8      ; form logical address into R0
    chkl R2,Rss_limit     ; Check logical address against segment lower
                           limit
    chku R2,R_FFFFFFFF    ; Check logical address against segment upper
                           limit
30  add  R3,R2,Rss_base   ; add segment base to form linear address
    ld   Reax,[R3]        ; load s from memory address in R3 into Ra

    mov  [%eax], %ecx     // store c into [s]
35  chku Reax,Rds_limit   ; Check logical address against segment upper
                           limit
    add  R4,Reax,Rds_base ; add segment base to form linear address
    st   [R4],Recx        ; store c into memory address s
40  add  %eax, #4         // increment s by 4
    addcc Reax,Reax,4      ; increment s by 4

45  mov  [%ebp+0x8], %eax // store (s + 4) to memory

```

```

    add    R5,Rebp,0x8      ; form logical address into R5
    chkl   R5,Rss_limit     ; Check logical address against segment lower
                           ; limit
5    chku   R5,R_FFFFFFFF   ; Check logical address against segment upper
                           ; limit
    add    R6,R5,Rss_base   ; add segment base to form linear address
    st     [R6],Reax        ; store (s + 4) to memory address in R6

10    mov   %eax, [%ebp+0x10] // load n

    add    R7,Rebp,0x10     ; form logical address into R7
    chkl   R7,Rss_limit     ; Check logical address against segment lower
                           ; limit
15    chku   R7,R_FFFFFFFF   ; Check logical address against segment upper
                           ; limit
    add    R8,R7,Rss_base   ; add segment base to form linear address
    ld     Reax, [R8]       ; load n from memory address in R8 into Reax

20    lea    %ecx, [%eax-1]  // decrement n

    sub    Recx,Reax,1      ; decrement n

    mov     [%ebp+0x10], %ecx // store (n - 1)

25    add    R9,Rebp,0x10     ; form logical address into R9
    chkl   R9,Rss_limit     ; Check the logical address against segment
                           ; lower limit
    chku   R9,R_FFFFFFFF   ; Check logical address against segment upper
                           ; limit
30    add    R10,R9,Rss_base ; add segment base to form the linear address
    st     [R10],Recx       ; store n-1 in Recx into memory using address
                           ; in R10

35    and    %eax, %eax      // test n to set condition codes

    andcc   R11,Reax,Reax   ; test n to set condition codes

    jg      -.0x1b          // branch to top of this section if "n>0"

40    jg      mainloop,mainloop ; jump to main loop

Host Instruction key:
    chkl + check lower limit
45    chku = check upper limit

```

The next sample illustrates for each of the primitive target instructions the addition of host primitive instructions by which addresses needed for the target operation may be generated by the code morphing software. It should be noted that host address generation instructions are only required in an embodiment of a

microprocessor in which code morphing software is used for address generation rather than address generation hardware. In a target processor such as an X86 microprocessor these addresses are generated using address generation hardware. Whenever address generation occurs in such an embodiment of the invention, the calculation is accomplished; and host primitive instructions are also added to check the address values to determine that the calculated addresses are within the appropriate X86 segment limits.

10 **Adds instructions to maintain the target X86 instruction pointer "eip" and the commit instructions that use the special morph host hardware to update X86 state.**

```

mov %ecx, [%ebp+0xc] // load c

    add    R0, Rebp, 0xc
15    chk1   R0, Rss_limit
    chku   R0, R_FFFFFFFF
    add    R1, R0, Rss_base
    ld     Recx, [R1]
    add    Reip, Reip, 3          ; add X86 instruction length to eip in Reip
20    commit                          ; commits working state to official state

mov %eax, [%ebp+0x8] // load s

    add    R2, Rebp, 0x8
25    chk1   R2, Rss_limit
    chku   R2, R_FFFFFFFF
    add    R3, R2, Rss_base
    ld     Reax, [R3]
    add    Reip, Reip, 3          ; add X86 instruction length to eip in Reip
30    commit                          ; commits working state to official state

mov [%eax], %ecx // store c into [s]

    chku   Reax, Rds_limit
35    add    R4, Reax, Rds_base
    st     [R4], Recx
    add    Reip, Reip, 2          ; add X86 instruction length to eip in Reip
    commit                          ; commits working state to official state

40    add %eax, #4 // increment s by 4

    addcc  Reax, Reax, 4
    add    Reip, Reip, 5          ; add X86 instruction length to eip in Reip
    commit                          ; commits working state to official state
45    mov [%ebp+0x8], %eax // store (s + 4)

    add    R5, Rebp, 0x8

```



```

    chkl  R5,Rss_limit
    chku  R5,R_FFFFFFFF
    add   R6,R5,Rss_base
    st    [R6],Reax
5   add   Reip,Reip,3      ; add X86 instruction length to eip in Reip
    commit                                ; commits working state to official state

    mov   %eax, [%ebp+0x10] // load n

10  add   R7,Rebp,0x10
    chkl  R7,Rss_limit
    chku  R7,R_FFFFFFFF
    add   R8,R7,Rss_base
    ld    Reax,[R8]
15  add   Reip,Reip,3      ; add X86 instruction length to eip in Reip
    commit                                ; commits working state to official state

    lea   %ecx, [%eax-1]   // decrement n

20  sub   Recx,Reax,1
    add   Reip,Reip,3      ; add X86 instruction length to eip in Reip
    commit                                ; commits working state to official state

    mov   [%ebp+0x10], %ecx // store (n - 1)

25  add   R9,Rebp,0x10
    chkl  R9,Rss_limit
    chku  R9,R_FFFFFFFF
    add   R10,R9,Rss_base
30  st    [R10],Recx
    add   Reip,Reip,3      ; add X86 instruction length to eip in Reip
    commit                                ; commits working state to official state

    and   %eax,%eax        // test n

35  andcc R11,Reax,Reax
    add   Reip,Reip,3
    commit                                ; commits working state to official state

40  jg    -.0x1b           // branch "n>0"

    add   Rseq,Reip,Length(jg)
    ldc   Rtarg,EIP(target)
    selcc Reip,Rseq,Rtarg
45  commit                                ; commits working state to official state
    jg    mainloop,mainloop

Host Instruction key:
    commit = copy contents of working registers to official target
50  registers and send working stores to memory

```

This sample illustrates the addition of two steps to each set of primitive host instructions to update the official target registers after

the execution of the host instructions necessary to carry out each primitive target instruction and to commit the uncommitted values in the gated store buffer to memory. As may be seen, in each case, the length of the target instruction is added to the value in the working instruction pointer register (Reip). Then a commit instruction is
5 executed. In one embodiment, the commit instruction copies the current value of each working register which is shadowed into its associated official target register and moves a pointer value designating the position of the gate of the gated store buffer from
10 immediately in front of the uncommitted stores to immediately behind those stores so that they will be placed in memory.

It will be appreciated that the list of instructions illustrated last above are all of the instructions necessary to form a host translation of the original target assembly language instructions. If the translation were
15 to stop at this point, the number of primitive host instructions would be much larger than the number of target instructions (probably six times as many instructions), and the execution could take longer than execution on a target processor. However, at this point, no reordering, optimizing, or rescheduling has yet taken place.

20 If an instruction is to be run but once, it may be that the time required to accomplish further reordering and other optimization is greater than the time to execute the translation as it exists at this point. If so, one embodiment of the present invention ceases the translation at this point, stores the translation, then executes it to
25 determine whether exception or errors occur. In this embodiment, steps of reordering and other optimization only occur if it is determined that the particular translation will be run a number times or otherwise should be optimized. This may be accomplished, for example by placing host instructions in each translation which count
30 the number of times a translation is executed and generate an

exception (or branch) when a certain value is reached. The exception (or branch) transfers the operation to the code morphing software which then implements some or all of the following optimizations and any additional optimizations determined useful for that translation. A

5 second method of determining translations being run a number of times and requiring optimization is to interrupt the execution of translations at some frequency or on some statistical basis and optimize any translation running at that time. This would ultimately provide that the instructions most often run would be optimized.

10 Another solution would be to optimize each of certain particular types of host instructions such as those which create loops or are otherwise likely to be run most often.

Optimization

15 **Assumes 32 bit flat address space which allows the elimination of segment base additions and some limit checks.**

Win32 uses Flat 32b segmentation

20 *Record Assumptions:*

Rss_base==0

Rss_limit==0

Rds_base==0

Rds_limit==FFFFFFFF

25 *SS and DS protection check*

mov %ecx,[%ebp+0xc] // load c

30 **add R0,Rebp,0xc**
chku R0,R_FFFFFFFF
ld Recx,[R0]
add Reip,Reip,3
commit

35 **mov %eax,[%ebp+0x8] // load s**

add R2,Rebp,0x8
chku R2,R_FFFFFFFF
 40 **ld Reax,[R2]**
add Reip,Reip,3
commit

mov [%eax],%ecx // store c into [s]

45 **chku Reax,R_FFFFFFFF**

```

    st    [Reax], Recx
    add   Reip, Reip, 2
    commit

5    add   %eax, #4           // increment s by 4

    addcc Reax, Reax, 4
    add   Reip, Reip, 5
    commit
10

    mov   [%ebp+0x8], %eax    // store (s + 4)

    add   R5, Rbp, 0x8
    chku  R5, R_FFFFFFFF
15    st    [R5], Reax
    add   Reip, Reip, 3
    commit

    mov   %eax, [%ebp+0x10]    // load n
20

    add   R7, Rbp, 0x10
    chku  R7, R_FFFFFFFF
    ld    Reax, [R7]
    add   Reip, Reip, 3
25    commit

    lea   %ecx, [%eax-1]      // decrement n

    sub   Recx, Reax, 1
30    add   Reip, Reip, 3
    commit

    mov   [%ebp+0x10], %ecx    // store (n - 1)

35    add   R9, Rbp, 0x10
    chku  R9, R_FFFFFFFF
    st    [R9], Recx
    add   Reip, Reip, 3
    commit
40

    and   %eax, %eax          // test n

    andcc R11, Reax, Reax
    add   Reip, Reip, 3
45    commit

    jg    .-0x1b              // branch "n>0"

50    add   Rseq, Reip, Length(jg)
    ldc   Rtarg, EIP(target)
    selcc Reip, Rseq, Rtarg
    commit
    jg    mainloop, mainloop

```

This sample illustrates a first stage of optimization which may be practiced utilizing the present invention. This stage of optimization, like many of the other operations of the code morphing software, assumes an optimistic result. The particular optimization assumes
5 that a target application program which has begun as a 32 bit program written for a flat memory model provided by the X86 family of processors will continue as such a program. It will be noted that such an assumption is particular to the X86 family and would not necessarily be assumed with other families of processors being
10 emulated.

If this assumption is made, then in X86 applications all segments are mapped to the same address space. This allows those primitive host instructions required by the X86 segmentation process to be eliminated. As may be seen, the segment values are first set to zero.
15 Then, the base for data is set to zero, and the limit set to the maximum available memory. Then, in each set of primitive host instructions for executing a target primitive instruction, the check for a segment base value and the computation of the segment base address required by segmentation are both eliminated. This reduces
20 the loop to be executed by two host primitive instructions for each target primitive instruction requiring an addressing function. At this point, the host instruction check for the upper memory limit still exists.

It should be noted that this optimization requires the speculation
25 noted that the application utilizes a 32 bit flat memory model. If this is not true, then the error will be discovered as the main loop resolves the destination of control transfers and detects that the source assumptions do not match the destination assumptions. A new

translation will then be necessary. This technique is very general and can be applied to a variety of segmentation and other "moded" cases where the "mode" changes infrequently, like debug, system management mode, or "real" mode.

5 **Assume data addressed includes no bytes outside of computer memory limits which can only occur on unaligned page crossing memory references at the upper memory limit, and can be handled by special case software or hardware.**

```

10     mov %ecx, [%ebp+0xc] // load c

       add R0, Rebp, 0xc
       ld  Recx, [R0]
       add Reip, Reip, 3
15     commit

       mov %eax, [%ebp+0x8] // load s

       add R2, Rebp, 0x8
20     ld  Reax, [R2]
       add Reip, Reip, 3
       commit

       mov [%eax], %ecx // store c into [s]

25     st  [Reax], Recx
       add Reip, Reip, 2
       commit

30     add %eax, #4 // increment s by 4

       addcc Reax, Reax, 4
       add Reip, Reip, 5
       commit

35     mov [%ebp+0x8], %eax // store (s + 4)

       add R5, Rebp, 0x8
       st  [R5], Reax
40     add Reip, Reip, 3
       commit

       mov %eax, [%ebp+0x10] // load n

45     add R7, Rebp, 0x10
       ld  Reax, [R7]
       add Reip, Reip, 3
       commit

50     lea %ecx, [%eax-1] // decrement n

```

```

sub    Recx, Reax, 1
add    Reip, Reip, 3
commit

5    mov    [%ebp+0x10], %ecx // store (n - 1)

add    R9, Rebp, 0x10
st     [R9], Recx
add    Reip, Reip, 3
10   commit

and    %eax, %eax          // test n

andcc  R11, Reax, Reax
add    Reip, Reip, 3
15   commit

jg     .-0x1b              // branch "n>0"

20   add    Rseq, Reip, Length(jg)
ldc    Rtarg, EIP(target)
selcc  Reip, Rseq, Rtarg
commit
jg     mainloop, mainloop
25

Host Instruction key:
      selcc = Select one of source registers and copy its contents to
              destination register based on condition codes.

```

30 The above sample illustrates a next stage of optimization in which a speculative translation eliminates the upper memory boundary check which is only necessary for unaligned page crossing memory references at the top of the memory address space. Failure of this assumption is detected by either hardware or software alignment fix

35 up. This reduces the translation by another host primitive instruction for each target primitive instruction requiring addressing. This optimization requires both the assumption noted before that the application utilizes a 32 bit flat memory model and the speculation that the instruction is aligned. If these are not both true, then the

40 translation will fail when it is executed; and a new translation will be necessary.

Detect and eliminate redundant address calculations. The example shows the code

after eliminating the redundant operations.

```

mov  %ecx, [%ebp+0xc] // load c

5   add  R0, Rebp, 0xc
    ld   Recx, [R0]
    add  Reip, Reip, 3
    commit

10  mov  %eax, [%ebp+0x8] // load s

    add  R2, Rebp, 0x8
    ld   Reax, [R2]
    add  Reip, Reip, 3
15  commit

    mov  [%eax], %ecx      // store c into [s]

    st   [Reax], Recx
    add  Reip, Reip, 2
    commit

    add  %eax, #4          // increment s by 4

25  addcc Reax, Reax, 4
    add  Reip, Reip, 5
    commit

    mov  [%ebp+0x8], %eax // store (s + 4)

30  st   [R2], Reax
    add  Reip, Reip, 3
    commit

35  mov  %eax, [%ebp+0x10] // load n

    add  R7, Rebp, 0x10
    ld   Reax, [R7]
    add  Reip, Reip, 3
40  commit

    lea  %ecx, [%eax-1]    // decrement n

    sub  Recx, Reax, 1
    add  Reip, Reip, 3
    commit

45  mov  [%ebp+0x10], %ecx // store (n - 1)

    st   [R7], Recx
    add  Reip, Reip, 3
    commit

50  and  %eax, %eax        // test n

55

```



```

andcc R11, Reax, Reax
add   Reip, Reip, 3
commit

5   jg    -.0x1b           // branch "n>0"

    add   Rseq, Reip, Length(jg)
    ldc   Rtarg, EIP(target)
    selcc Reip, Rseq, Rtarg
10   commit
    jg    mainloop, mainloop

```

This sample illustrates a next optimization in which common host expressions are eliminated. More particularly, in translating the second target primitive instruction, a value in working register Rebp (the working register representing the stack base point register of an X86 processor) is added to an offset value 0x8 and placed in a host working register R2. It will be noted that the same operation took place in translating target primitive instruction five in the previous sample except that the result of the addition was placed in working register R5. Consequently the value to be placed in working register R5 already exists in working register R2 when host primitive instruction five is about to occur. Thus, the host addition instruction may be eliminated from the translation of target primitive instruction five; and the value in working register R2 copied to working register R5. Similarly, a host instruction adding a value in working register Rebp to an offset value 0x10 may be eliminated in the translation of target primitive instruction eight because the step has already been accomplished in the translation of target primitive instruction six and the result resides in register R7. It should be noted that this optimization does not depend on speculation and consequently is not subject to failure and retranslation.

Assume that target exceptions will not occur within the translation so delay updating eip and target stat .

```

    m v %ecx,[%ebp+0xc] // load c
    add R0,Rebp,0xc
5    ld  Recx,[R0]

    mov %eax,[%ebp+0x8] // load s
    add R2,Rebp,0x8
10   ld  Reax,[R2]

    mov [%eax],%ecx      // store c into [s]
    st   [Reax],Recx
15

    add %eax,#4          // increment s by 4
    add Reax,Reax,4

    mov [%ebp+0x8],%eax // store (s + 4)
    st   [R2],Reax

    mov %eax,[%ebp+0x10] // load n
25   add R7,Rebp,0x10
    ld  Reax,[R7]

    lea %ecx,[%eax-1]    // decrement n
30   sub Recx,Reax,1

    mov [%ebp+0x10],%ecx // store (n - 1)
    st   [R7],Recx
35

    and %eax,%eax        // test n
    andcc R11,Reax,Reax
40

    jg  -.0x1b           // branch "n>0"
    add Rseq,Reip,Length(block)
    ldc Rtarg,EIP(target)
45   selcc Reip,Rseq,Rtarg
    commit
    jg  mainloop,mainloop

```

The above sample illustrates an optimization which speculates that
 50 the translation of the primitive target instructions making up the

entire translation may be accomplished without generating an exception. If this is true, then there is no need to update the official target registers or to commit the uncommitted stores in the store buffer at the end of each sequence of host primitive instructions which carries out an individual target primitive instruction. If the speculation holds true, the official target registers need only be updated and the stores need only be committed once, at the end of the sequence of target primitive instructions. This allows the elimination of two primitive host instructions for carrying out each primitive target instruction. These are replaced by a single host primitive instruction which updates the official target registers and commits the uncommitted stores to memory.

As will be understood, this is another speculative operation which is also highly likely to involve a correct speculation. This step offers a very great advantage over all prior art emulation techniques if the speculation holds true. It allows all of the primitive host instructions which carry out the entire sequence of target primitive instructions to be grouped in a sequence in which all of the individual host primitives may be optimized together. This has the advantage of allowing a great number of operations to be run in parallel on a morph host which takes advantage of the very long instruction word techniques. It also allows a greater number of other optimizations to be made because more choices for such optimizations exist. Once again, however, if the speculation proves untrue and an exception is taken when the loop is executed, the official target registers and memory hold the official target state which existed at the beginning of the sequence of target primitive instructions since a commit does not occur until the sequence of host instructions is actually executed. All that is

necessary to recover from an exception is to dump the uncommitted stores, rollback the official registers into the working registers, and restart translation of the target primitive instructions at the beginning of the sequence. This re-translation produces a translation of one
 5 target instruction at a time, and the official state is updated after the host sequence representing each target primitive instruction has been translated. This translation is then executed. When the exception occurs on this re-translation, correct target state is immediately available in the official target registers and memory for carrying out
 10 the exception.

In summary:

```

      add    R0,Rebp,0xc
      ld     Recx,[R0]
15      add    R2,Rebp,0x8
      ld     Reax,[R2]
      st     [Reax],Recx
      add    Reax,Reax,4
      st     [R2],Reax
20      add    R7,Rebp,0x10
      ld     Reax,[R7]           // Live out
      sub    Recx,Reax,1         // Live out
      st     [R7],Recx
      andcc  R11,Reax,Reax
25      add    Rseq,Reip,Length(block)
      ldc    Rtarg,EIP(target)
      selcc  Reip,Rseq,Rtarg
      commit
30      jg     mainloop,mainloop
  
```

The comment "Live Out" refers to the need to actually maintain Reax and Recx correctly prior to the commit. Otherwise further optimization might be possible.

35

The summary above illustrates the sequence of host primitive instructions which remain at this point in the optimization process. While this example shows the maintenance of the target instruction pointer (EIP) inline, it is possible to maintain the pointer EIP for
 40 branches out of line at translation time, which would remove the

pointer EIP updating sequence from this and subsequent steps of the example.

Renaming to reduce register resource dependencies. This will allow subsequent scheduling to be more effective. From this point on, the original target X86 code is omitted as the relationship between individual target X86 instructions and host instructions becomes increasingly blurred.

```

5      add    R0,Rebp,0xc
      ld     R1,[R0]
10     add    R2,Rebp,0x8
      ld     R3,[R2]
      st     [R3],R1
      add    R4,R3,4
      st     [R2],R4
15     add    R7,Rebp,0x10
      ld     Reax,[R7]          // Live out
      sub    Recx,Reax,1        // Live out
      st     [R7],Recx
      andcc  R11,Reax,Reax
20     add    Rseq,Reip,Length(block)
      ldc    Rtarg,EIP(target)
      selcc  Reip,Rseq,Rtarg
      commit
      jg     mainloop,mainloop
25

```

This sample illustrates a next step of optimization, normally called register renaming, in which operations requiring working registers used for more than one operation in the sequence of host primitive instructions are changed to utilize a different unused working register to eliminate the possibility that two host instructions will require the same hardware. Thus, for example, the second host primitive instruction in two samples above uses working register Recx which represents an official target register ECX. The tenth host primitive instruction also uses the working register Recx. By changing the operation in the second host primitive instruction so that the value pointed to by the address in R0 is stored in the working register R1 rather than the register Recx, the two host instructions do not both use the same register. Similarly, the fourth, fifth, and sixth host primitive instructions all utilize the working register Reax in the

earlier sample; by changing the fourth host primitive instruction to utilize the previously unused working register R3 instead the working register Reax and the sixth host primitive instruction to utilize the previously unused working register R4 instead of the register Reax, these hardware dependencies are eliminated.

After the scheduling process which organizes the primitive host operations as multiple operations that can execute in the parallel on the host VLIW hardware. Each line shows the parallel operations that the VLIW machine executes, and the "&" indicates the parallelism.

```

10      add    R2,Rebp,0x8      & add R0,Rebp,0xc
      nop                                & add R7,Rebp,0x10
      ld     R3,[R2]          & add Rseq,Reip,Length(block)
      ld     R1,[R0]          & add R4,R3,4
15      st     [R3],R1        & ldc Rtarg,EIP(target)
      ld     Reax,[R7]        & nop
      st     [R2],R4          & sub Recx,Reax,1
      st     [R7],Recx        & andcc R11,Reax,Reax
20      selcc Reip,Rseq,Rtarg  & jg  mainloop,mainloop & commit

```

Host Instruction key:
nop = no operation

The above sample illustrates the scheduling of host primitive instructions for execution on the morph host. In this example, the morph host is presumed to be a VLIW processor which in addition to the hardware enhancements provided for cooperating with the code morphing software also includes, among other processing units, two arithmetic and logic (ALU) units. The first line illustrates two individual add instructions which have been scheduled to run together on the morph host. As may be seen, these are the third and the eight primitive host instructions in the sample just before the summary above. The second line includes a NOP instruction (no operation but go to next instruction) and another add instruction. The NOP instruction illustrates that there are not always two instructions which can be run together even after some scheduling

optimizing has taken place. In any case, this sample illustrates that only nine sets of primitive host instructions are left at this point to execute the original ten target instructions.

Resolve host branch targets and chain stored translations

```

5      add    R2,Rebp,0x8          & add R0,Rebp,0xc
      nop                                & add R7,Rebp,0x10
      ld     R3,[R2]              & add Rseq,Reip,Length(block)
      ld     R1,[R0]              & add R4,R3,4
10     st     [R3],R1              & ldc Rtarg,EIP(target)
      ld     Reax,[R7]            & nop
      st     [R2],R4              & sub Recx,Reax,1
      st     [R7],Recx            & andcc R11,Reax,Reax
      selcc Reip,Rseq,Rtarg       & jg Sequential,Target & commit
15

```

This sample illustrates essentially the same set of host primitive instructions except that the instructions have by now been stored in the translation buffer and executed one or more times because the last jump (jg) instruction now points to a jump address furnished by chaining to another sequence of translated instructions. The chaining process takes the sequence of instructions out of the translator main loop so that translation of the sequence has been completed.

Advanced Optimizations, Backward Code Motion:

25 This and subsequent examples start with the code prior to scheduling. This optimization first depends on detecting that the code is a loop. Then invariant operations can be moved out of the loop body and executed once before entering the loop body.

```

30  Entry:
      add    R0,Rebp,0xc
      add    R2,Rebp,0x8
      add    R7,Rebp,0x10
      add    Rseq,Reip,Length(block)
35  ldc     Rtarg,EIP(target)

```

```

      Loop:
      ld     R1,[R0]
      ld     R3,[R2]
40  st     [R3],R1
      add    R4,R3,4
      st     [R2],R4
      ld     Reax,[R7]
      sub    Recx,Reax,1

```

```

    st    [R7], Recx
    andcc R11, Reax, Reax
    selcc Reip, Rseq, Rtarg
    commit
5      jg    mainloop, Loop

```

The above sample illustrates an advanced optimization step which is usually only utilized with sequences which are to be repeated a large number of times. The process first detects translations that form loops, and reviews the individual primitives host instructions to determine which instructions produce constant results within the loop body. These instructions are removed from the loop and executed only once to place a value in a register; from that point on, the value stored in the register is used rather than rerunning the instruction.

15 **Schedule the loop body after backward code motion.** For example purposes, only the code in the loop body is shown scheduled

```

Entry:
20      add    R0, Rbp, 0xc
        add    R2, Rbp, 0x8
        add    R7, Rbp, 0x10
        add    Rseq, Reip, Length(block)
        ldc    Rtarg, EIP(target)

25      Loop:
        ld     R3, [R2]           & nop
        ld     R1, [R0]           & add R4, R3, 4
        st     [R3], R1           & nop
        ld     Reax, [R7]         & nop
30      st     [R2], R4           & sub Recx, Reax, 1
        st     [R7], Recx         & andcc R11, Reax, Reax
        selcc Reip, Rseq, Rtarg   & jg Sequential, Loop    & commit

35      Host Instruction key:
        ldc = load a 32-bit constant

```

When these non-repetitive instructions are removed from the loop and the sequence is scheduled for execution, the scheduled instructions appear as in the last sample above. It can be seen that the initial instructions are performed but once during the first iteration of the

loop and thereafter only the host primitive instructions remaining in the seven clock intervals shown are executed during the loop. Thus, the execution time has been reduced to seven instruction intervals from the ten instructions necessary to execute the primitive target instructions.

As may be seen, the steps which have been removed from the loop are address generation steps. Thus, address generation only need be done once per loop invocation in the present invention; that is, the address generation need only be done one time. On the other hand, the address generation hardware of the X86 target processor must generate these addresses each time the loop is executed. If a loop is executed one hundred times, the present invention generates the addresses only once while a target processor would generate each address one hundred times.

15 After Backward Code Motion:

Target:

```

    add    R0, Rebp, 0xc
    add    R2, Rebp, 0x8
20      add    R7, Rebp, 0x10
    add    Rseq, Reip, Length(block)
    ldc    Rtarg, EIP(target)

```

Loop:

```

25      ld     R1, [R0]
    ld     R3, [R2]
    st     [R3], R1
    add    R4, R3, 4
    st     [R2], R4
30      ld     Reax, [R7]           //Live out
    sub    Recx, Reax, 1           //Live out
    st     [R7], Recx
    andcc  R11, Reax, Reax
    selcc  Reip, Rseq, Rtarg
35      commit
    jg     mainloop, Loop

```

Register allocation:

40 This shows the use of register alias detection hardware of the morph host that allows variables to be safely moved from memory into registers. The starting point is the code after "backward code

motion". This shows the optimization that can eliminate loads.

First the loads are performed. The address is protected by the alias hardware, such that should a store to the address occur, an "alias" exception is raised. The loads in the loop body are then replaced with copies. After the main body of the loop, the alias hardware is freed.

```

5      Entry:
10      add    R0,Rebp,0xc
      add    R2,Rebp,0x8
      add    R7,Rebp,0x10
      add    Rseq,Reip,Length(block)
15      ldc    Rtarg,EIP(target)

      ld     Rc,[R0]      ;First do the load of variable from memory
      prot   [R0],Alias1 ;Then protect memory location from stores

20      ld     Rs,[R2]
      prot   [R2],Alias2

      ld     Rn,[R7]
      prot   [R7],Alias3

25      Loop:
      copy   R1,Rc
      copy   R3,Rs
      st     [R3],R1
      add    R4,Rs,4
30      copy   Rs,R4
      st     [R2],Rs,NoAliasCheck
      copy   Reax,Rn
      sub    Recx,Reax,1      //Live out
      copy   Rn,Recx          //Live out
35      st     [R7],Rn,noAliasCheck
      andcc  R11,Reax,Reax
      selcc  Reip,Rseq,Rtarg
      commit
40      jg     Epilog,Loop

      Epilog:
      FA     Alias1      Free the alias detection hardware
      FA     Alias2      Free the alias detection hardware
45      FA     Alias3      Free the alias detection hardware
      j      Sequential

```

Host Instruction key:

protect = protect address from loads
copy = copy j = jump

FA = free alias

50 This sample illustrates an even more advanced optimization which may be practiced by the microprocessor of the present invention. Referring back to the second sample before this sample, it will be noticed that the first three add instructions involved computing

addresses on the stack. These addresses do not change during the execution of the sequence of host operations. Consequently, the values stored at these addresses may be retrieved from memory and loaded in registers where they are immediately available for execution.

5 As may be seen, this is done in host primitive instructions six, eight, and ten. In instructions seven, nine and eleven, each of the memory addresses is marked as protected by special host alias hardware and the registers are indicated as aliases for those memory addresses so that any attempt to vary the data will cause an exception. At this
10 point, each of the load operations involving moving data from these stack memory addresses becomes a simple register-to-register copy operation which proceeds much faster than loading from a memory address. It should be noted that once the loop has been executed until $n=0$, the protection must be removed from each of the memory
15 addresses so that the alias registers may be otherwise utilized.

Copy Propagation :

After using the alias hardware to turn loads within the loop body into copies, copy propagation allows the elimination of some copies.

20

Entry:

25 add R0,Rebp,0xc
 add R2,Rebp,0x8
 add R7,Rebp,0x10
 add Rseq,Reip,Length(block)
 ldc Rtarg,EIP(target)

30 ld Rc,[R0]
 prot [R0],Alias1

 ld Rs,[R2]
 prot [R2],Alias2

35 ld Recx,[R7]
 prot [R7],Alias3

Loop:

40 st [Rs],Rc
 add Rs,Rs,4
 st [R2],Rs,NoAliasCheck
 copy Reax,Recx //Live out
 sub Recx,Reax,1 //Live out

```

    st      [R7], Recx, NoAliasCheck
    andcc   R11, Reax, Reax
    selcc   Reip, Rseq, Rtarg
    commit
5      jg     Epilog, Loop

Epilog:
    FA      Alias1
    FA      Alias2
10     FA      Alias3
    j       Sequential

```

This sample illustrates the next stage of optimization in which it is recognized that most of the copy instructions which replaced the load instructions in the optimization illustrated in the last sample are unnecessary and may be eliminated. That is, if a register-to-register copy operation takes place, then the data existed before the operation in the register from which the data was copied. If so, the data can be accessed in the first register rather than the register to which it is being copied and the copy operation eliminated. As may be seen, this eliminates the first, second, fifth, and ninth primitive host instructions shown in the loop of the last sample. In addition, the registers used in others of the host primitive instructions are also changed to reflect the correct registers for the data. Thus, for example, when the first and second copy instructions are eliminated, the third store instruction must copy the data from the working register Rc where it exists (rather than register R1) and place the data at the address indicated in working register Rs where the address exists (rather than register R3).

30 **Example illustrating scheduling of the loop body only .**

```

Entry:
    add     R0, Rbp, 0xc
    add     R2, Rbp, 0x8
35     add     R7, Rbp, 0x10
    add     Rseq, Reip, Length(block)
    ldc     Rtarg, EIP(target)

```

```

        ld    Rc, [R0]
        prot  [R0], Alias1

        ld    Rs, [R2]
        prot  [R2], Alias2

        ld    Recx, [R7]
        prot  [R7], Alias3

Loop:
10      st     [Rs], Rc,          & add Rs, Rs, 4          & copy
      Reax, Recx
        st     [R2], Rs, NAC      & sub Recx, Reax, 1
        st     [R7], Recx, NAC    & andcc R11, Reax, Reax
        selcc  Reip, Rseq, Rtarg  & jg  Epilog, Loop      & commit
15      Epilog:
        FA     Alias1
        FA     Alias2
        FA     Alias3
        j      Sequential
20

Host Instruction key:
      NAC= No Alias Check

```

The scheduled host instructions are illustrated in the sample above.

It will be noted that the sequence is such that fewer clocks are required to execute the loop than to execute the primitive target instruction originally decoded from the source code. Thus, apart from all of the other acceleration accomplished, the total number of combined operations to be run is simply less than the operations necessary to execute the original target code.

Store Elimination by use of the alias hardware.

```

Entry:
35      add    R0, Rbp, 0xc
        add    R2, Rbp, 0x8
        add    R7, Rbp, 0x10
        add    Rseq, Reip, Length(block)
        ldc    Rtarg, EIP(target)

40      ld     Rc, [R0]
        prot   [R0], Alias1          ;protect address from loads and stores

        ld     Rs, [R2]
        prot   [R2], Alias2          ;protect address from loads and stores
45      ld     Recx, [R7]
        prot   [R7], Alias3          ;protect address from loads and stores

```

```

Loop:
    st      [Rs], Rc,          & add Rs, Rs, 4          & copy
Reax, Recx
    sub     Recx, Reax, 1       & andcc R11, Reax, Reax
5    selcc  Reip, Rseq, Rtarg   & jg  Epilog, Loop       & commit
Epilog:
    FA      Alias1
    FA      Alias2
    FA      Alias3
10    st     [R2], Rs           ;writeback final value of Rs
    st     [R7], Recx          ;writeback final value of Recx
    j       Sequential

```

The final optimization shown in this sample is the use of the alias hardware to eliminate stores. This eliminates the stores from within the loop body, and performs them only in the loop epilog. This reduces the number of host instructions within the loop body to three compared to the original ten target instructions.

Although the present invention has been described in terms of a preferred embodiment, it will be appreciated that various modifications and alterations might be made by those skilled in the art without departing from the spirit and scope of the invention. For example, although the invention has been described with relation to the emulation of X86 processors, it should be understood that the invention applies just as well to programs designed for other processor architectures, and programs that execute on virtual machines, such as P code, Postscript, or Java programs. The invention should therefore be measured in terms of the claims which follow.

What Is Claimed Is:

Claim 1. A microprocessor comprising the combination of translation software, and

host hardware,

the translation software running directly on the host hardware.

Claim 2 A microprocessor as claimed in Claim 1 in which the translation software is code morphing software and the host hardware is morph host hardware

Claim 3. A microprocessor as claimed in Claim 2 in which the code morphing software comprises:

processes to translate target instructions of a program written for a processor having a first instruction set into primitive
5 instructions capable of execution on the enhanced morph host hardware, and

processes to store the host primitive instructions as host translations in a translation buffer from which they may be recalled and executed by the morph host hardware any number
10 of times.

Claim 4. A microprocessor as claimed in Claim 3 in which the code morphing software further comprises processes to reorder, reschedule and optimize the primitive host instructions.

Claim 5. A microprocessor as claimed in Claim 2 in which the enhanced morph host hardware comprises:

a store buffer for data being transferred to memory, the store buffer including:

5 means responding to execution of a host translation
without an exception to commit data stored in the store
buffer to memory, and

means responding to generation of an exception or error
during execution of a host translation to dump data in the
10 store buffer without committing it to memory;

an execution unit comprising:

a set of working registers in the execution unit larger than
a set of registers required by a target processor in a target
processor execution unit;

15 a set of target registers for holding official register state of
a target processor developed in processing a target
program; and

in which the code morphing software comprises:

20 means responding to execution of a host translation
without an exception or error during execution of a host
translation for transferring state from the sets of working
registers to the target registers, and

25 means responding to generation of an exception or error
during execution of a host translation for transferring
state from the sets of target registers to the sets of
working registers.

Claim 6. A microprocessor as claimed in Claim 5:

- in which the means responding to execution of a host translation without an exception or error during execution of a host translation for transferring state from the sets of working registers to the target registers comprises a commit host instruction,
- 5 in which the means responding to generation of an exception or error during execution of a host translation for transferring state from the sets of target registers to the sets of working registers comprises a rollback host instruction, and
- 10 in which the means responding to execution of a host translation without an exception to commit data stored in the store buffer to memory, and the means responding to generation of an exception or error during execution of a host translation to dump data in the store buffer without committing it to memory function in response to the
- 15 commit host instruction and the rollback host instruction.

Claim 7. A microprocessor as claimed in Claim 5 in which the enhanced morph host hardware comprises means indicating that a target instruction has been translated.

Claim 8. A microprocessor as claimed in Claim 5 in which the means indicating that a target instruction has been translated includes an address translation cache storing an indication that a target instruction has been translated.

Claim 9. A microprocessor as claimed in Claim 5 in which the enhanced morph host hardware comprises means indicating that an instruction is normal or abnormal.

Claim 10. A microprocessor as claimed in Claim 8 in which the means indicating that an instruction is normal or abnormal includes

an address translation cache storing an indication that a target instruction has been translated.

Claim 11. A microprocessor as claimed in Claim 5 in which the enhanced morph host hardware comprises means indicating that data at a memory address has been moved to a register.

Claim 12. A microprocessor as claimed in Claim 11 in which the means indicating that data at a memory address has been moved to a register includes means storing an indication that data at the address has been moved to a register comprises means for comparing
5 addresses to be executed with an address of data which has been moved to a register.

Claim 13. A microprocessor as claimed in Claim 2 in which the enhanced morph host hardware comprises a very long instruction word microprocessor.

Claim 14. A microprocessor for a host computer designed to execute target application programs for a target computer having a target instruction set comprising the combination of:

code morphing software, and

5 morph host processing hardware designed to execute instructions of a host instruction set,

the combination of the code morphing software and the morph host processing hardware comprising:

10 means to translate a set of target instructions into instructions of a host instruction set speculating upon the occurrence of a condition,

means to determine under control of the code morphing
software official state of the target computer which existed at
the beginning of a translation of a set of target instructions
15 during execution of the target program by the microprocessor,

means for updating state of the target computer from state of
the host computer when a set of host instructions executes in
accordance with the speculation,

means to detect failure of the condition during the execution of
20 the set of host instructions,

means for updating state of the host computer from state of the
target computer when a set of host instructions fails to execute
in accordance with the speculation, and

means to translate a new set of host instructions without the
25 speculation when a set of host instructions fails to execute in
accordance with the speculation.

Claim 15. A microprocessor for a host computer as claimed in Claim
14 further comprising means to optimize the instructions of the host
instruction set translated from the target program speculating upon
the occurrence of a condition.

Claim 16. A microprocessor for a host computer as claimed in Claim
14 in which the means to translate a set of target instructions into
instructions of a host instruction set speculating upon the occurrence
of a condition speculates that no exception or error will occur during
5 the translation of the set of instructions.

Claim 17. A microprocessor for a host computer as claimed in Claim 14 in which the means to determine under control of the code morphing software official state of the target computer which existed at the beginning of a translation of a set of target instructions
5 comprises means storing official state of the target computer which existed at the beginning of a translation of a set of target instructions.

Claim 18. A microprocessor for a host computer as claimed in Claim 17 in which the means storing official state of the target computer which existed at the beginning of a translation of a set of target instructions comprises a set of target registers.

Claim 19. A microprocessor for a host computer as claimed in Claim 17 in which the means for updating state of the target computer from state of the host computer when a set of host instructions executes in accordance with the speculation comprises means for transferring
5 host state to the means storing official state of the target computer when a set of host instructions executes without an error or exception.

Claim 20. A microprocessor for a host computer as claimed in Claim 14 in which the means to detect failure of the condition during the execution of the set of host instructions comprises means generating an exception.

Claim 21. A microprocessor for a host computer as claimed in Claim 20 in which the means generating an exception is hardware means.

Claim 22. A microprocessor for a host computer as claimed in Claim 20 in which the means generating an exception is software means.

Claim 23. A microprocessor for a host computer as claimed in Claim 14 in which the means for updating state of the host computer from

state of the target computer when a set of host instructions fails to execute in accordance with the speculation comprises means
5 transferring official state of the target computer which existed at the beginning of a translation of a set of target instructions to update host state.

Claim 24. A microprocessor for a host computer as claimed in Claim 14 in which the means to translate a new set of host instructions without the speculation when a set of host instructions fails to execute in accordance with the speculation comprises means
5 beginning at a target instruction which existed at the beginning of a translation of a set of target instructions which failed to translate each target instruction in order saving host state as official state of the target computer.

Claim 25. A method of executing target programs designed to be executed by a target computer having a target instruction set on a host computer having a host processor capable of executing instructions from a host instruction set different than the target
5 instruction set, the method comprising:

storing state of the target computer as it exists at the beginning of translating a target instruction;

translating target instructions commanding an operation into a set of host instructions for executing on the host processor the operation
10 commanded by the target instruction;

storing the host instructions as a host translation in a translation buffer;

executing the host translation on the host processor;

updating state stored for the target computer from state of the host
15 computer when the execution of a host translation does not generate
an exception or error; and

updating state of the host computer from stored state of the target
computer when the execution of the host translation generates an
exception or error.

Claim 26. A method of executing target application programs as
claimed in Claim 25 comprising the additional step of optimizing and
rescheduling host instructions before storing the set of host
instructions as a host translation.

Claim 27. A method of executing target application programs as
claimed in Claim 25 comprising the additional steps of:

translating each target instructions commanding an operation into a
set of host instructions for executing on the host processor each target
5 instruction of the operation commanded by the target instructions
without reordering, optimizing, or rescheduling the primitive
instructions to generate a host instruction;

storing each set of host instructions in the translation buffer as a host
translation as the set is completed;

10 storing and updating state of the host computer after each target
instruction is translated to a set of host instructions,

executing each host translation on the host processor;

updating state stored for the target computer from state of the host
computer when the execution of a host translation does not generate
15 an exception or error; and

taking any exception or error generated when executing the host instruction generates an exception or an error.

Claim 28. A method of executing target application programs as claimed in Claim 25 comprising the additional step of optimizing and rescheduling host instructions after storing the set of host instructions as a host translation if the set of host instructions is to
5 be reexecuted often.

1/7

Target Application
Target Oper. Sys.
Target Hardware

Intel

Figure 1a

Target Application
Part Target OpSys
Emulator
Host Oper. Sys.
Host Hardware

SoftPC

Figure 1b

Target Application
Part Target OpSys
Emulator
Part Host Op Sys
Host Hardware

Apple

Figure 1c

Target Application
Emulator
Host Oper. Sys.
Host Hardware

DEC

Figure 1d

Target Application
Emulator
Host Oper. Sys.
Host Hardware

Shade

Figure 1

2/7




Figure 2




Figure 3




Figure 4




Figure 5




Figure 10

4/7




Figure 6c




Figure 6a






Figure 6b

5/7

**Figure 7**

6/7

**Figure 8**

7/7




Figure 9

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/11616

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06F 9/45

US CL : 395/705

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 395/705, 500, 704,800.01,800.23,800.24

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS,STN (FILE COMPUTER)

Search terms: emulaion,host,target,translation,conversion, code morphing

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X, P	US 5,574,927 A (SCANTLIN) 12 November 1996, col. 2 lines 30- col. 3 line 42, col. 4 line 34 - col. 5 line 2.	1-2
A	HALFHILL T. R. , EMULATION: RISC's Secret Weapon, BYTE, April 1994. Pages 119-130, especially pages 119-120.	1-28
A	ANDREWS K. et al., Migrating a CISC Computer Family onto RISC via Object Code Translation, ASPLOS V 1992 ACM. The abstract	1-28
A	CMELIK R. et al., Shade : A Fast Instruction Set Simulator for Execution Profiling, ACM 1994, the Abstract.	1-28

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

05 DECEMBER 1997

Date of mailing of the international search report

04 MAR 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer
E. TODD VOELTZ

Telephone No. (703) 305-9600

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/11616

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	BEDICHEK R.C., Talisman : Fast and Accurate Multicomputer Simulation, MIT 1995, the Abstract.	1-28